Product datasheet

Specification





TeSys D contactor - 4P(2 NO + 2 NC) - AC-1 - <= 440 V 125 A - 110 V DC coil

LP1D80008FD

Main

Range	TeSys	
Range of product	TeSys Deca	
Product or component type	Contactor	
Device short name	LP1D	
contactor application	Resistive load	
Utilisation category	AC-1	
poles description	4P	
[Ue] rated operational voltage	Power circuit: <= 690 V AC 25400 Hz	
[le] rated operational current	125 A (at <60 °C) at <= 440 V AC AC-1 for power circuit	
[Uc] control circuit voltage	110 V DC	

Complementary

Compatibility code	LP1D
Pole contact composition	2 NO + 2 NC
Protective cover	Without
[Ith] conventional free air thermal current	125 A (at 60 °C) for power circuit
Irms rated making capacity 1100 A at 440 V for power circuit conforming to IEC 60947	
Rated breaking capacity	1100 A at 440 V for power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	135 A 40 °C - 10 min for power circuit 320 A 40 °C - 1 min for power circuit 640 A 40 °C - 10 s for power circuit 990 A 40 °C - 1 s for power circuit
Associated fuse rating	200 A gG at <= 690 V coordination type 1 for power circuit 160 A gG at <= 690 V coordination type 2 for power circuit
Average impedance 0.8 mOhm - Ith 125 A 50 Hz for power circuit	
Power dissipation per pole	12.5 W AC-1
[Ui] rated insulation voltage	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Power circuit: 1000 V conforming to IEC 60947-4-1
Overvoltage category	III
Pollution degree	3
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947
Safety reliability level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1

Mechanical durability	10 Mcycles
Electrical durability	0.8 Mcycles 125 A AC-1 at Ue <= 440 V
Control circuit type	DC DC standard
Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.10.3 Uc (-4055 °C):drop-out DC 0.851.1 Uc (-4055 °C):operational DC
Inrush power in W	22 W (at 20 °C)
Hold-in power consumption in W	22 W at 20 °C
Operating time	620 ms opening 2035 ms closing
Time constant	75 ms
Maximum operating rate	3600 cyc/h 60 °C
Connections - terminals	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end Power circuit: connector 2 425 mm² - cable stiffness: flexible without cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 416 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 450 mm² - cable stiffness: solid Power circuit: connector 2 425 mm² - cable stiffness: solid Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with cable end
Tightening torque	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Power circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
Mounting support	Rail Plate
Environment	
Standards	CSA C22.2 No 14 EN 60947-4-1
	EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Product certifications	EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1
Product certifications IP degree of protection	EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 UL CSA CCC EAC UKCA CB DNV-GL RINA BV
	EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 UL CSA CCC EAC UKCA CB DNV-GL RINA BV LROS (Lloyds register of shipping)
IP degree of protection Permissible ambient air	EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 UL CSA CCC EAC UKCA CB DNV-GL RINA BV LROS (Lloyds register of shipping) IP20 front face conforming to IEC 60529 -4060 °C

V1 conforming to UL 94

Flame retardance

Mechanical robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (3 Gn, 5300 Hz) Shocks contactor open (8 Gn for 11 ms) Shocks contactor closed (10 Gn for 11 ms)	
Height	127 mm	
Width	96 mm	
Depth	196 mm	
Net weight	2.91 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.5 cm
Package 1 Width	11.0 cm
Package 1 Length	14.0 cm
Package 1 Weight	2.804 kg

Contractual warranty

Warranty 18 months

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc
⊘	Toxic Heavy Metal Free
⊘	Mercury Free
⊘	Rohs Exemption Information Yes
Ø	Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations