

# Product data sheet

Specifications



## Differential thermal overload relays, TeSys K, 5.5 to 8 A, class 10A

LR2K0314

Product availability : Stock - Normally stocked in distribution facility

Price\* : 59.00 USD

### Main

Range	TeSys
Product name	TeSys LRK
Product or Component Type	Differential thermal overload relay
Device short name	LR2K
Relay application	Motor protection
Product Compatibility	LC7K LC1K LP4K LP1K
Network type	DC AC
Thermal overload class	Class 10A IEC 60947-4-1
Thermal protection adjustment range	5.5...8 A
[Ui] rated insulation voltage	Power circuit 690 V BS 4941 Power circuit 690 V IEC 60947 Power circuit 750 V VDE 0110 group C Power circuit 600 V CSA C22.2 No 14

### Complementary

Network Frequency	<= 400 Hz
Mounting support	Under contactor Plate, with specific accessories Rail, with specific accessories
Auxiliary contact composition	1 NO + 1 NC
[Ith] conventional free air thermal current	6 A signalling circuit
[Ue] rated operational voltage	<= 690 V power circuit 690 V AC AC-15 signalling circuit 250 V DC DC-13 signalling circuit
Associated fuse rating	6 A gG signalling circuit VDE 0660 6 A gG signalling circuit IEC 60947
[Uimp] rated impulse withstand voltage	6 kV
Power dissipation per pole	2 W
Phase failure sensitivity	Yes IEC 60947-4-1

\* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Local signalling	Trip indicator Yellow)
Control type	Red push-button trip test function Blue push-button stop and manual reset selector switch manual or automatic reset
Connections - terminals	screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1.5...4 mm <sup>2</sup> )solid screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1.5...4 mm <sup>2</sup> )solid screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (0.75...4 mm <sup>2</sup> )flexible without cable end screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (0.75...4 mm <sup>2</sup> )flexible without cable end screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (0.34...2.5 mm <sup>2</sup> )flexible with cable end screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (0.34...1.5 mm <sup>2</sup> )flexible with cable end
Tightening torque	11.51 lbf.in (1.3 N.m) screw clamp terminals Philips No 2 11.51 lbf.in (1.3 N.m) screw clamp terminals flat Ø 6 mm 11.51 lbf.in (1.3 N.m) screw clamp terminals pozidriv No 2
Height	2.28 in (58 mm)
Width	1.77 in (45 mm)
Depth	2.56 in (65 mm)
Net Weight	0.32 lb(US) (0.145 kg)

## Environment

Standards	VDE 0660 NF C 63-650 IEC 60947 BS 4941
Product Certifications	UL CSA UKCA
Protective treatment	TC IEC 60068 TC DIN 50016
IP degree of protection	IP2X conforming to IEC 60529
Ambient air temperature for operation	-4...131 °F (-20...55 °C) without derating IEC 60947 -22...140 °F (-30...60 °C) with derating IEC 60947
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Operating altitude	6561.68 ft (2000 m) without derating
Fire resistance	1562 °F (850 °C) IEC 60695-2-1
Flame retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102
Mechanical robustness	Shocks NO contact10 Gn for 11 ms IEC 60068-2-27 Shocks NC contact10 Gn for 11 ms IEC 60068-2-27 Vibrations NO contact2 Gn, 5...300 Hz IEC 60068-2-6 Vibrations NC contact2 Gn, 5...300 Hz IEC 60068-2-6

## Ordering and shipping details

Category	22324-CONTACTOR,K-LINE,OVERLOADS
Discount Schedule	I12
GTIN	3389110230574
Returnability	Yes
Country of origin	CZ

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.97 in (5.000 cm)
Package 1 Width	2.80 in (7.100 cm)
Package 1 Length	3.23 in (8.200 cm)

Package 1 Weight	5.61 oz (159.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	41
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	14.89 lb(US) (6.756 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

### Contractual warranty

Warranty	18 months
----------	-----------

### Recommended replacement(s)