Product datasheet

Specification





circuit breaker Compact NSXm 160A 4P 50kA at 380/415V(IEC) EverLink lug

LV426429

! Discontinued on: 15 Jun 2023

① Discontinued

Main

| Range | ComPact | |
|--|--|--|
| Product Name | ComPact NSXm | |
| Range Of Product | ComPact NSXm | |
| Device Short Name | NSXm 160N | |
| Product Or Component Type | Circuit breaker | |
| Device Application | Protection Distribution | |
| Number Of Poles | 4P | |
| Protected Poles Description | 4D | |
| Neutral Position | Left | |
| [In] Rated Current | 160 A at 40 °C | |
| [Ue] Rated Operational Voltage | 690 V AC 50/60 Hz | |
| Network Type | AC | |
| Network Frequency | 50/60 Hz | |
| Suitability For Isolation | Yes conforming to EN/IEC 60947-2 | |
| Utilisation Category | Category A | |
| [Icu] Rated Ultimate Short-Circuit Breaking Capacity | 90 kA Icu at 220240 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 380415 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 | |
| Performance Level | N 50 kA 415 V AC | |
| Trip Unit Name | TM-D | |
| Trip Unit Technology | Thermal-magnetic | |
| Trip Unit Protection Functions | Ш | |
| Control Type | Toggle | |
| Circuit Breaker Mounting Mode | By screws Clip-on | |

Complementary

| [Ui] Rated Insulation Voltage | 800 V AC 50/60 Hz |
|--|--|
| [Uimp] Rated Impulse Withstand Voltage | 8 kV |
| [Ics] Rated Service Short-Circuit Breaking Capacity | 90 kA at 220240 V AC 50/60 Hz conforming to IEC 60947-2 50 kA at 380415 V AC 50/60 Hz conforming to IEC 60947-2 50 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 |

8 Nov 2023 Life Is On Schneider

| Mechanical Durability | 20000 cycles |
|--|---|
| Electrical Durability | 10000 cycles at 440 V In 20000 cycles at 440 V In/2 5000 cycles at 690 V In 10000 cycles at 690 V In/2 |
| Mounting Support | Plate DIN rail |
| Connection Terminals | 1 Everlink lug wire size 2.570 mm², flexible copper 1 Everlink lug wire size 2.595 mm², rigid or stranded copper |
| Connection Pitch | 35 mm with spreaders 27 mm without spreaders |
| 9 Mm Pitches | 12 module |
| Protection Type | L : for overload protection (thermal) I : for short-circuit protection (magnetic) |
| Trip Unit Rating | 160 A at 40 °C |
| Long-Time Pick-Up Adjustment Type Ir (Thermal Protection) | Adjustable |
| [Ir] Long-Time Protection Pick-Up Adjustment Range | 0.71 x ln |
| Long-Time Protection Delay Adjustment Type Tr | Fixed |
| [Im] Magnetic Protection Pick-Up Range | 1250 A |
| Earth-Leakage Protection | Without |
| Number Of Slots For Electrical Auxiliaries | 1 slot(s) for auxiliary switch OF 1 slot(s) for alarm switch SD 1 slot(s) for voltage release MN or MX |
| Width (W) | 108 mm |
| Height (H) | 137 mm |
| Depth (D) | 80 mm |
| Net Weight | 1.42 kg |
| Colour | Grey (RAL 7016) |

Environment

| Standards | EN/IEC 60947 | |
|---------------------------------------|---|--|
| Product Certifications | CCC EAC Marine | |
| Pollution Degree | 3 conforming to IEC 60664-1 | |
| Ip Degree Of Protection | IP40 conforming to IEC 60529 | |
| Ik Degree Of Protection | IK07 conforming to IEC 62262 | |
| Ambient Air Temperature For Operation | -2570 °C | |
| Ambient Air Temperature For Storage | -5085 °C | |
| Relative Humidity | 095 % | |
| Operating Altitude | 02000 m without derating 20005000 m with derating | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----|
| Number Of Units In Package 1 | 1 |

| Package 1 Height | 12.0 cm |
|------------------------------|----------|
| Package 1 Width | 12.0 cm |
| Package 1 Length | 22.0 cm |
| Package 1 Weight | 1.6 kg |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 6 |
| Package 2 Height | 30 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 10.19 kg |

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more >





Transparency RoHS/REACh

Well-being performance

Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |