Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

undervoltage release (spring) MN - 380...415 V AC 50Hz



LV426806

Main

Range	ComPact
Range Of Product	ComPacT NSXm new generation
Device Short Name	MN
Product Or Component Type	Voltage release
Device Application	Control
Voltage Release Type	Opening coil Undervoltage release
Control Type	Standard
[Uc] Control Circuit Voltage	380415 V AC 50 Hz
Range Compatibility	ComPact ComPacT NSXm new generation ComPact ComPact NSXm PowerPact PowerPact B

Complementary

Operating Threshold	0.350.7 x Un opening 0.85 x Un closing
Response Time	< 50 ms
Auxiliary Connection Terminal	Carina

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6 cm
Package 1 Length	8.3 cm
Package 1 Weight	62 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	20
Package 2 Height	8.5 cm
Package 2 Width	13 cm
Package 2 Length	18.5 cm
Package 2 Weight	1.3 kg
Unit Type Of Package 3	S03

Number Of Units In Package 3	120
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	8.2 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more >

Well-being performance

