

shunt trip (spring) MX-208...240 V AC 60Hz-220...240 50Hz-277 V AC 60Hz-250 V DC

LV426844

Range	ComPact
Range of product	ComPacT NSXm new generation
Device short name	MX
Product or component type	Voltage release
Device application	Control
Voltage release type	Opening coil Shunt trip release
Control type	Standard
[Uc] control circuit voltage	220240 V AC 50 Hz 208240 V AC 60 Hz 277 V AC 60 Hz 250 V DC
Range compatibility	ComPact ComPacT NSXm new generation ComPact ComPact NSXm PowerPact PowerPact B

Complementary

Operating threshold	0.7 Un opening
Response time	< 50 ms
Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Auxiliary connection terminal	Spring

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6 cm
Package 1 Length	8.5 cm
Package 1 Weight	63 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10

Package 2 Height	9 cm
Package 2 Width	8 cm
Package 2 Length	14 cm
Package 2 Weight	681 g
Unit Type of Package 3	S03
Number of Units in Package 3	80
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	5.82 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)