

# Product datasheet

Specifications



## MX shunt trip release, Compact NSX, PowerPact Multistandard, EasyPact CVS, rated voltage 60 VDC

LV429383

### Main

Range	ComPacT
Range of product	ComPacT NSX100...250 ComPacT NSX100...250 new generation ComPacT NSX400...630 ComPacT NSX400...630 new generation ComPacT NSX100...250 DC ComPacT NSX100...250 DC new generation ComPacT NSX100...250 DC PV ComPacT NSX100...250 DC PV new generation ComPacT NSX400...630 DC ComPacT NSX400...630 DC new generation ComPacT NSX400...630 DC PV ComPacT NSX400...630 DC PV new generation
Device short name	MX
Product or component type	Voltage release
Device application	Control
Voltage release type	Opening coil Shunt trip release
[Uc] control circuit voltage	60 V DC
Range compatibility	ComPacT new generation ComPacT NSX new generation ComPacT new generation ComPacT NSX DC new generation ComPacT ComPacT NSX ComPacT ComPacT NSX DC EasyPact EasyPact CVS PowerPact PowerPact Multistandard

### Complementary

Operating threshold	0.7...1.1 x Un opening
Response time	50 ms
Control signal type	Maintained Impulse
Impulse duration	>= 20 ms
Supply inrush power	10 W
Auxiliary connection terminal	Spring 0.5...1.5 mm <sup>2</sup> (AWG 20...AWG 16)
Wire stripping length	7 mm

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	6.3 cm
Package 1 Width	4 cm
Package 1 Length	8 cm
Package 1 Weight	123 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9 cm
Package 2 Width	14.8 cm
Package 2 Length	22.5 cm
Package 2 Weight	1.327 kg
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	8.45 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)