MX shunt trip release, Compact NSX, PowerPact Multistandard, EasyPact CVS, rated voltage 125 **VDC** 

LV429393

Range	ComPacT
Range of product	ComPact NSX100250
	ComPacT NSX100250 new generation
	ComPact NSX400630
	ComPacT NSX400630 new generation
	ComPact NSX100250 DC
	ComPacT NSX100250 DC new generation
	ComPact NSX100250 DC PV
	ComPacT NSX100250 DC PV new generation
	ComPact NSX400630 DC
	ComPacT NSX400630 DC new generation
	ComPact NSX400630 DC PV
	ComPacT NSX400630 DC PV new generation
Device short name	MX
Product or component type	Voltage release
Device application	Control
Voltage release type	Opening coil
	Shunt trip release
[Uc] control circuit voltage	125 V DC
Range compatibility	ComPacT new generation ComPacT NSX new generation
	ComPacT new generation ComPacT NSX DC new generation
	ComPact ComPact NSX
	ComPact ComPact NSX DC
	EasyPact EasyPact CVS
	PowerPact PowerPact Multistandard

### Complementary

Operating threshold	0.71.1 x Un opening
Response time	50 ms
Control signal type	Maintained Impulse
Impulse duration	>= 20 ms
Supply inrush power	10 W
Auxiliary connection terminal	Spring 0.51.5 mm² (AWG 20AWG 16)
Wire stripping length	7 mm

### **Packing Units**

Unit Type of Package 1	PCE
Nonellan af Halla in Bankana 4	

Number of Units in Package 1

Package 1 Height	4.2 cm
Package 1 Width	6.2 cm
Package 1 Length	7.8 cm
Package 1 Weight	126 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.4 cm
Package 2 Width	14.8 cm
Package 2 Length	22.4 cm
Package 2 Weight	1.344 kg
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	8.551 kg

# Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

## **Contractual warranty**

Warranty 18 months

Recommended replacement(s)