

Product datasheet

Specifications



insulation monitoring module,
ComPact NSX 100/160/250, 200
VAC to 440 VAC 50/60 Hz, 0.1 A to
1 A, 4 poles

LV429460

⚠ Discontinued

⚠ Discontinued on: 18 January 2022

Main

Product or component type	Insulation monitoring device
Device application	Insulation
Range compatibility	ComPact ComPact NSX100 ComPact ComPact NSX160 ComPact ComPact NSX250
Poles description	4P

Complementary

[Ue] rated operational voltage	200...440 V
Network type	AC
Network frequency	50/60 Hz
Measurement accuracy	-50 %...0 %
Residual earth-leakage sensitivity adjustment type	Adjustable
[IΔn] residual earth-leakage sensitive adjustment	0.1 A 0.2 A 0.5 A 1 A
[Δt] residual earth-leakage time delay adjustment	5...10 s

Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

Contractual warranty

Warranty18 months

Recommended replacement(s)