

Product datasheet

Specifications



circuit breaker Compact NSX250B,
25 kA at 415 VAC, TMD trip unit 250
A, 3 poles 3d

LV431110

⚠ Discontinued on: 31 December 2022

⚠ To be discontinued

Main

| | |
|--|--|
| Range | ComPact |
| Product name | ComPact NSX |
| Range of product | ComPact NSX100...250 |
| Device short name | NSX250B |
| Product or component type | Circuit breaker |
| Device application | Distribution |
| Number of poles | 3P |
| Protected poles description | 3t |
| [In] rated current | 250 A at 40 °C |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2 |
| Utilisation category | Category A |
| [Icu] rated ultimate short-circuit breaking capacity | 15 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 20 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 25 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 40 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level | B 25 kA 415 V AC |
| Trip unit name | TM-D |
| Trip unit technology | Thermal-magnetic |
| Trip unit protection functions | LI |
| Control type | Toggle |
| Circuit breaker mounting mode | Fixed |

Complementary

| | |
|---|--|
| [Ui] rated insulation voltage | 800 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV |
| [Ics] rated service short-circuit breaking capacity | 20 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 25 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 |

| | |
|---|--|
| | 40 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 15 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability | 20000 cycles |
| Electrical durability | 5000 cycles at 690 V In 10000 cycles at 690 V In/2 10000 cycles at 440 V In 20000 cycles at 440 V In/2 |
| Mounting support | Backplate |
| Upside connection | Front |
| Downside connection | Front |
| Connection pitch | 35 mm |
| Protection type | L : for overload protection (thermal) I : for short-circuit protection (magnetic) |
| Trip unit rating | 250 A at 40 °C |
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable |
| [Ir] long-time protection pick-up adjustment range | 0.7...1 x In |
| Long-time protection delay adjustment type tr | Fixed |
| [Tr] long-time protection delay adjustment range | 120...400 s at 1.5 x In 15 s at 6 x Ir |
| Short-time protection pick-up adjustment type Isd | Adjustable |
| [Isd] Short-time protection pick-up adjustment range | 5...10 x In |
| Short-time protection delay adjustment type tsd | Fixed |
| Earth-leakage protection | Without |
| Number of slots for electrical auxiliaries | 5 slot(s) |
| Width (W) | 105 mm |
| Height (H) | 161 mm |
| Depth (D) | 86 mm |
| Net weight | 2.4 kg |

Environment

| | |
|---------------------------------------|------------------------------|
| Standards | EN/IEC 60947 |
| Product certifications | CCC EAC Marine |
| Overvoltage category | Class II |
| Electrical shock protection class | Class II |
| Pollution degree | 3 conforming to IEC 60664-1 |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -50...85 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...2000 m without derating |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 13.7 cm |
| Package 1 Width | 11.4 cm |
| Package 1 Length | 18.9 cm |
| Package 1 Weight | 1.991 kg |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 12 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 40.0 cm |
| Package 2 Length | 60.0 cm |
| Package 2 Weight | 24.742 kg |

Offer Sustainability


| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Recommended replacement(s)

LV431110 is replaced by:

| | | |
|----|---|---|
| 1x |  | Circuit breaker, ComPacT NSX250B, 25kA/415VAC, 3 poles, TMD trip unit 250A C25B3TM250 |
|----|---|---|