# Product datasheet

Specifications

## Motor mechanism, 110...230VAC@50/60Hz, 110...230VDC

LV435010

## Main

| | |
|---|---|
| **Range** | EasyPact |
| **Product name** | EasyPact CVS |
| **Product or component type** | Motor mechanism |
| **Device short name** | motor mechanism module |
| **Product compatibility** | EasyPact CVS400...630 circuit-breaker |

## Complementary

| | |
|---|---|
| **Control type** | Local/remote control |
| **Control signal type** | Impulse and maintained |
| **[Uc] control circuit voltage** | 110...230 V AC 50/60 Hz<br>110...230 V DC |
| **mounting mode** | Fixed |
| **Response time** | <= 500 ms (opening)<br><= 1 s (closing) |
| **Maximum operating frequency** | <= 2 cycles per minute |
| **Maximum power consumption in VA** | 300 VA closing<br>300 VA opening |
| **Electrical durability** | 20000 cycles 110...230 V AC 50/60 Hz<br>20000 cycles 110...230 V DC |
| **Provided equipment** | Keylock |
| **Locking options description** | Transparent cover |
| **IK degree of protection** | IK07 |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 18.6 cm |
| **Package 1 Width** | 19.1 cm |
| **Package 1 Length** | 22.1 cm |
| **Package 1 Weight** | 2.6 kg |
| **Unit Type of Package 2** | S04 |
| **Number of Units in Package 2** | 3 |
| **Package 2 Height** | 30.0 cm |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Package 2 Width** | 40.0 cm |
| **Package 2 Length** | 60.0 cm |
| **Package 2 Weight** | 9.758 kg |
| **Unit Type of Package 3** | P12 |
| **Number of Units in Package 3** | 36 |
| **Package 3 Height** | 105.0 cm |
| **Package 3 Width** | 80.0 cm |
| **Package 3 Length** | 120.0 cm |
| **Package 3 Weight** | 129.096 kg |

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-$CO_2$ products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency RoHS/REACh

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

| | |
|---|---|
| **Eu Rohs Directive** | Compliant with Exemptions |
| **China Rohs Regulation** | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information |
| **Environmental Disclosure** | Product Environmental Profile |
| **Circularity Profile** | End of Life Information |