Product datasheet

Specification





Easypact CVS - CVS100F 6.2 100A circuit breaker - 4P

LV510639

Main

| Range | EasyPact |
|---------------------------|-----------------|
| Product Or Component Type | Circuit breaker |
| Device Short Name | CVS100F |
| Device Application | Distribution |

Complementary

| Poles Description Protected Poles Description Neutral Position Network Type | 3D + N/2 4D 3D Left |
|--|--|
| Neutral Position | 4D 3D Left |
| | 3D Left |
| | Left |
| | |
| Network Type | |
| Network Type | AC |
| Network Frequency | 50/60 Hz |
| Control Type | Toggle |
| Mounting Mode | Fixed |
| Mounting Support | Backplate |
| Upside Connection | Front |
| Downside Connection | Front |
| [In] Rated Current | 100 A at 40 °C |
| [Ui] Rated Insulation Voltage | 690 V AC 50/60 Hz conforming to EN/IEC 60947-2 |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV conforming to EN/IEC 60947-2 |
| [Ue] Rated Operational Voltage | 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 |
| Breaking Capacity Code | F |
| Breaking Capacity | 70 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 |
| | 50 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 |
| | 42 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] Rated Service Breaking | 70 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 |
| Capacity | 50 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 |
| | 32 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| Suitability For Isolation | Yes conforming to EN/IEC 60947-2 |
| Utilisation Category | Category A |
| Mechanical Durability | 30000 cycles |
| Electrical Durability | 12000 cycles 415 V In conforming to IEC 60947-2 30000 cycles 415 V In/2 conforming to IEC 60947-2 |

24-Jun-2024 Life Is On Schneider

| Connection Pitch | 35 mm |
|--|--|
| Trip Unit Name | ETS 6.2 |
| Trip Unit Technology | Electronic |
| Trip Unit Protection Functions | LSIG |
| Trip Unit Rating | 100 A at 40 °C |
| Protection Type | Ground fault protection Short time short-circuit protection Overload protection (long time) Instantaneous short-circuit protection |
| Long Time Pick-Up Adjustment Type Ir | Adjustable |
| Long Time Pick-Up Adjustment Range | 40100 A |
| Long Time Delay Adjustment Type | Adjustable |
| [Tr] Long-Time Delay Adjustment Range | 15400 s at 1.5 x lr 0.3511 s at 7.2 x lr 0.516 s at 6 x lr |
| Thermal Memory | 20 minutes before and after tripping |
| Short-Time Pick-Up Adjustment Type Isd | Adjustable |
| [Isd] Short-Time Pick-Up Adjustment Range | 1.510 x lr |
| Short-Time Delay Adjustment Type | Adjustable |
| [Tsd] Short-Time Delay Pick-Up | 00.4 s |
| Instantaneous Pick-Up Adjustment Type Ii | Adjustable |
| Instantaneous Pick-Up | 1.515 x In Easypact CVS100 |
| Ground-Fault Pick-Up Adjustment Type | Adjustable |
| Ground-Fault Time Delay Adjustment Type -Tg | Adjustable |
| [Tg] Ground-Fault Time Delay Adjustment Range | 00.4 s |
| [lg] Ground-Fault Pick-Up Adjustment Range | 20100 A |
| Zone Selective Interlocking Zsi | Without |
| Display Type | LCD display |
| Electrical Shock Protection Class | Class II |
| Electrical Data Recording | Maintenance indicators |
| Height | 161 mm |
| Width | 140 mm |
| Depth | 86 mm |

Environment

| Standards | EN 60947-2 IEC 60947-2 | |
|---------------------------------------|------------------------------|--|
| Product Certifications | СВ | |
| Ip Degree Of Protection | IP40 conforming to IEC 60529 | |
| Ik Degree Of Protection | IK07 conforming to IEC 62262 | |
| Pollution Degree | 3 conforming to IEC 60664-1 | |
| Ambient Air Temperature For Operation | -2570 °C | |

| Ambient Air Temperature For Storage | -5085 °C |
|-------------------------------------|----------|
| Net Weight | 2.05 kg |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|---------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 15.0 cm |
| Package 1 Width | 18.0 cm |
| Package 1 Length | 25.0 cm |
| Package 1 Weight | 2.5 kg |

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |