Product datasheet

Specification





circuit breaker EasyPact CVS250F, 36 kA at 415 VAC, 200 A rating thermal magnetic TM-D trip unit, 4P 3d

LV525342

Main

Range	EasyPact
Range of product	EasyPact CVS100250
Product name	EasyPact CVS
Device short name	CVS250F
product or component type	Circuit breaker
Device application	Distribution
poles description	4P
Protected poles description	3D
Earth leakage protection (Vigi add on)	Without
[In] rated current	200 A at 40 °C
Network type	AC
Utilisation category	Category A
[Icu] Breaking capacity	36 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 36 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 70 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit rating	200 A at 40 °C
Protection type	Short-circuit protection (magnetic) Overload protection (thermal)

Complementary

[Uimp] rated impulse withstand	8 kV conforming to EN/IEC 60947-2							
voltage Network frequency	50/60 Hz							
	30/00 Hz							
Breaking capacity code	F							
[Ics] rated service breaking	18 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2							
capacity	36 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2							
	70 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2							
Neutral position	Left							
Mechanical durability	20000 cycles							
Electrical durability	10000 cycles 415 V In conforming to IEC 60947-2							
Control type	Toggle							
Thermal protection adjustment range	140200 A							

04-Jul-2024 Life Is On Schneider

Neutral protection setting	No protection (3D)
Long time pick-up adjustment type Ir	Adjustable
Long time pick-up adjustment range	0.71 x ln
Long time delay adjustment type	Fixed
Instantaneous pick-up adjustment type li	Fixed
instantaneous pick-up adjustment range	2000 A
Contact position indicator	Yes
mounting support	Backplate
mounting mode	Fixed
Upside connection	Front
downside connection	Front
Connections - terminals	Screw connection
Connection pitch	35 mm
Compatibility code	CVS250
Width	140 mm
Depth	86 mm
Height	161 mm
net weight	2.2 kg

Environment

Standards	EN 60947-2 IEC 60947-2							
Product certifications	IEC GOST							
Electrical shock protection class	Class II							
Pollution degree	3 conforming to IEC 60664-1							
IP degree of protection	IP40							
Ambient air temperature for operation	-2570 °C							
Ambient air temperature for storage	-5085 °C							

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.800 cm
Package 1 Width	9.000 cm
Package 1 Length	13.800 cm
Package 1 Weight	2.600 kg
Unit Type of Package 2	S04
Number of Units in Package 2	9
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm

Package 2 Length	60.000 cm
Package 2 Weight	24.103 kg

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free




Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information


Dimensions Drawings





Туре	Α	A1	A2	A3	A4	A/5	A6	A7	A8	A9	В	B1	B2	C1	C2	C3	E1
CV9100160/250	66.5	161	64	146	179.5	155.5	226	169	226	250,5	52.5	105	946	-81	66	191@	62.5
C245/400/930	127.5	255	142,5	200	297	227.5	3.55	242.5	3.00	337	70	140	188	95.5	110	168	100
Type	E2	E3	E4	E5	E6	E7	E8	F1	F2	F3	G1	G2	G3	G4	G5	ØT	U
CW2100Y090/2800	125	हाड	140	137.5	200	148	215	216	17.5	70	96	78	13.5	25	17.5	24	y 32
CV5400/830	200	113.5	227	200	200	2135	327	45	22.5	90	-	00		-		32	y 35


[2] CJ-126mm for EasyPast CVS2509JF.

Assembly









Туре	Α	A1	A2	A3	A4	A5	A6	A7	A8	A9	В	B1	B2	C1	C2	C3	E1
CV8100160/250	66.5	161	64	146	179.5	155.5	236	169	226	250,5	52.5	105	146	81	06	1116	62.5
C2V5/400/930	127.5	296	142.原	200	297	227.6	3.55	242.5	3.00	337	70	140	188	95.5	110	168	100
Type	E2	E3	E4	E5	E6	E7	EB	F1	F2	F3	G1	G2	G3	G4	G5	ØT	U
CW9100/190/250	125	FE	140	137.5	200	145	215	216	17.5	70	56	78	13.5	25	17.5	24	y 32
CV\$400430	200	113.5	2028	200	300	213.5	327	45	22.5	90	-		-	-	-	32	y 35

[8] CJ-126mm for EasyPast CVS250fuF.

Performance Curves

