Product datasheet





circuit breaker, EasyPact CVS250B, 25kA at 415VAC, ETS 2.2, 250A, 4P

LV525508

Main

Range	EasyPact	
Range of product	EasyPact CVS100250	
Product name	EasyPact CVS	
Device short name	CVS250B	
Product or component type	Circuit breaker	
Device application	Distribution	
poles description	4P	
Protected poles description	3D 3D + N/2 4D	
Earth leakage protection (Vigi add on)	Without	
[In] rated current	250 A at 40 °C	
network type	AC	
Utilisation category	Category A	
[Icu] Breaking capacity	40 kA lcu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 25 kA lcu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 20 kA lcu at 440 V AC 50/60 Hz conforming to IEC 60947-2	
Trip unit name	ETS 2.2	
Trip unit technology	Electronic	
Protection type	Short time short-circuit protection with fixed delay Overload protection (long time) Instantaneous short-circuit protection	

Complementary

[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-2
Network frequency	50/60 Hz
Breaking capacity code	В
[lcs] rated service breaking capacity	15 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 25 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 40 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2
Neutral position	Left
Mechanical durability	20000 cycles
Electrical durability	10000 cycles 415 V In conforming to IEC 60947-2
Control type	Toggle
Neutral protection setting	No protection (3D)

Life Is On Schneider 8 Aug 2024

Long time pick-up adjustment type Ir	Adjustable 9 settings
Long time pick-up adjustment range	100250 A
Long time delay adjustment type	Fixed
[tr] long-time delay adjustment range	11 s at 7.2 x lr 16 s at 6 x lr 400 s at 1.5 x lr
Short-time pick-up adjustment type Isd	Adjustable 9 settings
[Isd] short-time pick-up adjustment range	1.510 x lr
Short-time delay adjustment type	Fixed
[tsd] short-time delay adjustment range	0.02 s
Instantaneous pick-up adjustment type li	Fixed
instantaneous pick-up adjustment range	3000 A
Contact position indicator	Yes
Mounting support	Backplate
Mounting mode	Fixed
Upside connection	Front
downside connection	Front
Connections - terminals	Screw connection
Connection pitch	35 mm
Compatibility code	CVS250
Width	140 mm
Depth	86 mm
Height	161 mm
Net weight	3.19 kg

Environment

Standards	EN 60947-2 IEC 60947-2
Product certifications	CCC CB
Electrical shock protection class	Class II
Pollution degree	3 conforming to IEC 60664-1
IP degree of protection	IP40
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-5085 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.000 cm
Package 1 Width	14.000 cm
Package 1 Length	19.000 cm

Package 1 Weight	2.647 kg
Unit Type of Package 2	S03
Number of Units in Package 2	4
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	11.400 kg
Unit Type of Package 3	P12
Number of Units in Package 3	32
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	100.640 kg

Sustainability Screen Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

8 Aug 2024