

Product datasheet

Specifications



Anti Harmonic detuned reactor 12.5kvar 190Hz (3.8) 7% 50Hz 400V

LVR07125A40T

Price* : 558.45 USD

Main

Range	PowerLogic
Device short name	DR
Product or component type	Detuned reactor
Network frequency	50 Hz
Reactive power rating	12.5 kvar for 400 V AC 50 Hz
Network rated voltage	400 V AC 50 Hz
Tuning order	3.8 - 190 Hz - 7 % - 50 Hz

Complementary

Power losses (max)	150 W
Value of inductance	2.987 mH
Inductance tolerance	- 5 % to 5 % per phase
Fundamental current rating	18 A
RMS current rating	19.5 A
Electrical insulation class	Class H
[Ui] rated insulation voltage	1.1 kV
Dielectric test voltage	4 kV 50 Hz 1 minute
[Imp] maximum permanent current	1.2 x I1
Harmonic current spectrum	3.7 % x I3 38.2 % x I5 13.6 % x I7 4.9 % x I11
Dynamic withstand current	2.2 x Isc
[Ith] conventional free air thermal current	2 A at 250 V AC 50 Hz
Type of installation	Indoor installation
Type of cooling	Forced convection
Connections - terminals	Pad terminal
Fixing center	200 x 125 mm
Height	220 mm

* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Width	240 mm
Depth	160 mm
Net weight	10 kg

Environment

Standards	IEC 60068
IP degree of protection	IP00
Operating altitude	<= 2000 m
Ambient air temperature for operation	0...55 °C at <= 1000 m 0...50 °C at > 1000...2000 m
Average ambient air temperature for operation	50 °C at <= 1000 m (average over 24 hours) 40 °C at <= 1000 m (average over 1 year) 45 °C at > 1000...2000 m (average over 24 hours) 35 °C at > 1000...2000 m (average over 1 year)
Climatic withstand	Relative humidity: 20...80 % Salt mist (400 V/50 Hz) : 250 hours

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.200 cm
Package 1 Width	29.200 cm
Package 1 Length	30.500 cm
Package 1 Weight	9.927 kg
Unit Type of Package 2	P12
Number of Units in Package 2	24
Package 2 Height	88.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	248.976 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)