Specifications



() Discontinued

# TeSys F - contactor coil - LX1FG -220...230 V AC 50 Hz - 265...277 V AC 60 Hz

LX1FG220

() Discontinued on: 18-Nov-2021

#### Main

TeSys	
Contactor coil	
LX1FG	
TeSys TeSys F LC1F contactor	
LC1F185 LC1F225	
AC at 50/60 Hz	
220230 V AC 50 Hz 265277 V AC 60 Hz	
2.59 H	
16.5 Ohm at 20 °C	
2035 ms closing 715 ms opening	
10 Mcycles	
2400 cyc/h 55 °C	

## Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.350.55 Uc 50/60 Hz (at 55 °C) Operational: 0.851.1 Uc 50/60 Hz (at 55 °C)
Inrush power in VA	805 VA 50 Hz cos phi 0.3 (at 20 °C) 970 VA 60 Hz cos phi 0.3 (at 20 °C)
Hold-in power consumption in VA	55 VA 50 Hz cos phi 0.3 (at 20 °C) 66 VA 60 Hz cos phi 0.3 (at 20 °C)
Heat dissipation	1824 W at 50/60 Hz

#### Environment

Ambient air temperature for operation	-555 °C
Net weight	0.55 kg

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7 cm

Package 1 Width	8 cm
Package 1 Length	16 cm
Package 1 Weight	545 g

### **Contractual warranty**

Warranty

18 months

#### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

# Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Eu R	Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
		EU RoHS Declaration
Chin	a Rohs Regulation	China RoHS declaration