

Product data sheet

Specifications



TeSys F - contactor coil - LX1FJ - 415...440V AC 40...400 Hz

LX1FJ415

Discontinued on: 15 June 2023

Product availability : Stock - Normally stocked in distribution facility

Discontinued

Main

Range	TeSys
Product or Component Type	Contactor coil
Device short name	LX1FJ
Range compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F400
Control circuit type	AC 40...400 Hz
[Uc] control circuit voltage	415...440 V AC 40...400 Hz
Inductance of closed circuit	19.4 H
Average resistance	145 Ohm inrush 68 °F (20 °C) 4070 Ohm holding 68 °F (20 °C)
Operating time	100...170 ms opening 40...75 ms closing
Mechanical durability	10 Mcycles
Maximum operating rate	2400 cyc/h 131 °F (55 °C)

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Operational 0.85...1.1 Uc 40...400 Hz 131 °F (55 °C)) Drop-out 0.3...0.5 Uc 40...400 Hz 131 °F (55 °C))
Inrush power in VA	1075 VA 40...400 Hz 0.9 68 °F (20 °C))
Hold-in power consumption in VA	15 VA 40...400 Hz 0.3 68 °F (20 °C))
Heat dissipation	14 W 40...400 Hz

Environment

Ambient air temperature for operation	23...131 °F (-5...55 °C)
Net Weight	2.20 lb(US) (1 kg)

Ordering and shipping details

Category	22341-CONTACTOR,D,K,&F ACCESS
----------	-------------------------------

Discount Schedule	I12
GTIN	3389110082081
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.30 in (18.542 cm)
Package 1 Width	3.60 in (9.144 cm)
Package 1 Length	4.00 in (10.16 cm)
Package 1 Weight	2.40 lb(US) (1.089 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	11.81 in (30 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	16.13 lb(US) (7.316 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)