# **Product datasheet**

Specification





## Control module, TeSys Giga, 100-250V AC/DC, for LC1G630-800/3P standard version

LX1G3TKUEN

#### Main

Range	TeSys	
Product or component type	Contactor coil	
Device short name	LX1G	
poles description	3P	
Range compatibility	TeSys G LX1G contactor coil	
Product compatibility	LC1G630800	
[Uc] control circuit voltage	100250 V AC/DC 50/60 Hz	
Operating time	2035 ms opening 4055 ms closing	
Mechanical durability	5 Mcycles	
Maximum operating rate	600 cyc/mn 60 °C	

## Complementary

Coil technology	Built-in bidirectional peak limiting
Control circuit voltage limits	Operational: 0.81.1 Uc (at 60 °C) Drop-out: 00.45 Uc (at 60 °C)
Connections - terminals	Control circuit: push-in termination 1 cable(s) 0.22.5 mm² solid stranded without cable end sleeve AWG 26AWG 12 Control circuit: push-in termination 1 cable(s) 0.252.5 mm² flexible with cable end sleeve AWG 24AWG 14 Control circuit: push-in termination 2 cable(s) 0.51.0 mm² rigid or stranded with cable end sleeve AWG 20AWG 18

### **Environment**

IP degree of protection	IP20 conforming to IEC 60529	
Operating altitude	3000 m without derating 5000 m with derating factor	
Electromagnetic compatibility	EMC immunity conforming to IEC 60947-4-1 Emission tests criteria A conforming to IEC 60947-4-1 Immunity to radiated radio-electrical interference - test level: 20 V/m conforming to EN/IEC 61000-4-3 Voltage dips and interruptions immunity test conforming to SEMI F47	
Standards	EN/IEC 60947-4-1 UL 60947-4-1A CSA C22.2 No 60947-4-1	
Pollution degree	3 conforming to IEC 60947-1	
Ambient air temperature for operation	-2560 °C	
Ambient air temperature for storage	-6080 °C	

Permissible ambient air temperature around the device	-4070 °C at Uc	
Height	130 mm	
Width	192 mm	
Depth	211 mm	
Net weight	2145 g	
Quantity per set	1	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22 cm
Package 1 Width	27 cm
Package 1 Length	29 cm
Package 1 Weight	2.5 kg



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>⊘</b>	Mercury Free
<b>②</b>	Rohs Exemption Information Yes
<b>9</b>	Pvc Free
<b>⊘</b>	Halogen Free Plastic Parts Product

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

## **Product datasheet**

### LX1G3TKUEN

Installation

**Installation Videos** 

TeSys Giga - How to replace control module