

TeSys F - contactor coil - LX4FF - 220...230 V DC

LX4FF220

! To be discontinued on: 31-Dec-2028

① To be discontinued

Main

| Range | TeSys | |
|------------------------------|--|--|
| Product or component type | Contactor coil | |
| Device short name | LX4FF | |
| Range compatibility | TeSys TeSys F LC1F contactor | |
| Product compatibility | LC1F115 LC1F150 | |
| Control circuit type | DC low consumption | |
| [Uc] control circuit voltage | 220230 V DC | |
| Inductance of closed circuit | 704 H | |
| Average resistance | 84 Ohm inrush at 20 °C 11100 Ohm holding at 20 °C | |
| Operating time | 3040 ms closing 3050 ms opening | |
| Mechanical durability | 10 Mcycles | |
| Maximum operating rate | 2400 cyc/h 55 °C | |

Complementary

| Coil technology | Without built-in suppressor module | |
|--------------------------------|---|--|
| Control circuit voltage limits | Operational: 0.851.1 Uc (at 55 °C) Drop-out: 0.150.2 Uc (at 55 °C) | |
| Inrush power in W | 560 W (at 20 °C) | |
| Hold-in power consumption in W | 4.5 W at 20 °C | |

Environment

| Ambient air temperature for operation | -555 °C |
|---------------------------------------|---------|
| Net weight | 0.43 kg |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|---------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.4 cm |
| Package 1 Width | 18.0 cm |
| Package 1 Length | 10.4 cm |

| Package 1 Weight | 506.0 g |
|------------------------------|---------|
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 14 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 7.61 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| Ø | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| Ø | Toxic Heavy Metal Free | |
| ⊘ | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |