Product data sheet

Specification





network switch, Modicon Networking, managed, 8 ports for copper with 4Gigabit SFP

MCSESM123F2LG0

Product availability: Stock - Normally stocked in distribution facility

Main

Range Of Product	Modicon
Product Or Component Type	Ethernet TCP/IP managed switch
Concept	Transparent Ready
Communication Port Protocol	Ethernet TCP/IP SSH HTTP HTTPS SNMP RS232 SFTP SCP LLDP Telnet SNTP
Port Ethernet	10/100BASE-TX - 8 copper cable 100/1000 SFP - 4
Maximum Number Of Switches In Cascade	Unlimited
Cybersecurity	Port hardening IP-based port security MAC-based port security Port-based access control Role-based access control RADIUS assignment HTTPS DoS prevention VLAN-based ACL Audit trail SNMP logging Pre-login banner

Complementary

J	
Integrated Connection Type	Shielded RJ45 copper cable SFP port fiber optic (Gbit)
Transmission Support Medium	Twisted shielded pairs cable CAT 5E copper cable Fiber optic cable fiber optic (Gbit)
Maximum Cable Distance Between Devices	328.08 ft (100 m) copper cable
Ethernet Service	Configuration via web server VLAN Multicast filtering Data stream control IGMP Snooping SNMP-Traps and SYSLOG
Communication Service	TFTP Quality of Service (QoS) Port monitoring Port mirroring Address conflict detection

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Diagnostics Pun Time	Signal contact
Diagnostics Run Time	Signal contact Self test
	MAC notification
Maximum Number Of Switches In A Ring	50
Redundancy	HiPER ring
	RSTP Link aggregation
	Link backup
	Redundant network coupling
	MRP
[Us] Rated Supply Voltage	1224 V
Supply Voltage Limits	9.632 V DC SELV
Power Consumption In W	9 W
Electrical Connection	Removable connector 6 ways power supply
Mounting Support	35 mm symmetrical DIN rail
Marking	CE
	CULus RCM
Function Available	Security status
	Alarms (Traps)
	System information Report
Local Signalling	for P1 P2 power supplies 1 dual colour LED (green/yellow)
	for device status 1 dual colour LED (green/red)
	for memory key status 1 dual colour LED (green/yellow) for channel diagnostic 1 dual colour LED (green/yellow)
Alarm Output	1 voltfree contact 1 A
Alarm Function	Power supply fault
	Data link status
	Switch fault
	Temperature threshold Redundancy ring fault
	Incorrect configuration
	External memory removed
Ethernet Cabling System	TF switches
Width	2.87 in (73 mm)
Height	5.62 in (142.8 mm)
Depth	4.63 in (117.6 mm)
Net Weight	1.26 lb(US) (0.57 kg)
Environment	
Ambient Air Temperature For Operation	32140 °F (060 °C)
Relative Humidity	195 % non-condensing
Ip Degree Of Protection	IP30
Directives	2014/35/EU - low voltage directive
	2014/30/EU - electromagnetic compatibility
Standards	UL 61010-2-201
	EN/IEC 61131-2 EN/IEC 62368-1
Product Certifications	CE
	UL
	RCM
	DNV ATEX

Ordering and shipping details

Category	US1PC1118121
Discount Schedule	PC11
Gtin	3606481463449
Returnability	Yes
Country Of Origin	DE

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.31 in (13.500 cm)
Package 1 Width	6.50 in (16.500 cm)
Package 1 Length	9.65 in (24.500 cm)
Package 1 Weight	28.50 oz (808.000 g)
Unit Type Of Package 2	S04
Number Of Units In Package 2	8
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	15.75 in (40.000 cm)
Package 2 Length	23.62 in (60.000 cm)
Package 2 Weight	16.27 lb(US) (7.382 kg)

Contractual warranty

Warranty 18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Weee Circularity Profile	· · · · · · · · · · · · · · · · · · ·

Dimensions Drawings

Dimensions

