Product datasheet





CONZERV EM6438H DUAL P&E RS485 CL 0.5

METSEEM6438HCL05RS

Main

Range	EasyLogic
Product Name	EasyLogic EM64XXH RS
Device Short Name	EM6438H
Product Or Component Type	Dual source energy meter

Complementary	
Device Application	Solar generation GenSet
	Main or redundant power monitoring
	Energy monitoring
	Wind generation
Type Of Measurement	Power factor
	Phase angle
	RPM
	Active power
	Active energy
Metering Type	Reactive power Q1, Q2
	Apparent power S, S1, S2, S3
	Active power P, P1, P2, P3
	Rotation speed
	Active, reactive, apparent energy (signed, two quadrant)
	Apparent energy (source 1)
	Alternate source meter
	Power factor and displacement PF (signed, four quadrant)
	Apparent energy (source 2)
Counter Functions	Alternate-source hour counting
	ON hour counting
[Us] Rated Supply Voltage	44300 V AC 4565 Hz
	44300 V DC
Network Frequency	50 Hz
	60 Hz
[In] Rated Current	5 A
• • • • • • • • • • • • • • • • • • • •	1 A
Type Of Network	2P
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	3P + N
	1P + N
	3P
	2P + N
Maximum Power Consumption In Va	4 VA at 240 V between phase and neutral
Maximum Power Consumption In W	2 W at 240 V
Display Type	7 segments LED
Display Colour	Red
Messages Display Capacity	3 fields of 4 characters

Life Is On Schneider 20-Apr-2024

Display Digits	12 digit(s) - 14.2 mm in height
Communication Of Data	Reading of measurements
	System power production
	All counters Last cleared log
	Revolution speed
Tamperproof Of Settings	Protected by access code
Sampling Rate	32 samples/cycle
Measurement Current	56000 mA
Signal	Voltage (impedance 5 MOhm)4 x
	Current 0.00510 A (impedance 0.3 MOhm)6 x
Measurement Voltage	46277 V AC 5060 Hz between phase and neutral
	80480 V AC 5060 Hz between phases
	277999000 V AC 5060 Hz with external VT
Frequency Measurement Range	4565 Hz
Measurement Accuracy	Power factor +/- 0.01
	Reactive power +/- 2 %
	Reactive energy +/- 2 % Active power +/- 0.5 %
	Apparent power +/- 0.5 %
	Active energy +/- 0.5 %
	Apparent energy +/- 0.5 %
Accuracy Class	Class 2 reactive energy conforming to IEC 62053-23
	Class 0.5 active energy conforming to IEC 62053-22
Number Of Outputs	0
Demand Intervals	1 s
Local Signalling	Green LED: activity Red LED: output signal 19999000 pulse/ k_h (kWh, kVAh, kVARh) Red LED: alternate source
Communication Port Protocol	Modbus at 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps even/odd or none - 2 wires, insulation 2500 V
Communication Port Support	Screw terminal block: RS485
Material	Polycarbonate
Flame Retardance	V-0 conforming to UL 94
Mounting Mode	Flush-mounted
Mounting Support	Framework
Fixing Mode	By clamp
Provided Equipment	Installation guide
Installation Category	III
Type Of Installation	Indoor installation
Measurement Category	Category III 35480 V
Electrical Insulation Class	Class II
Connections - Terminals	Current circuit: screw clamp terminals (bottom) 2.083.31 mm² cable(s) Voltage circuit: screw clamp terminals (top) 0.823.31 mm² cable(s) Control circuit: screw clamp terminals (top) 0.823.31 mm² cable(s) Communication: screw clamp terminals (bottom) 0.333.31 mm² cable(s) Secondary circuit: screw clamp terminals (bottom) 0.333.31 mm² cable(s)
Tightening Torque	Current circuit: 0.91 N.m Philips No 2 screwdriver Voltage circuit: 0.91 N.m Philips No 2 screwdriver Control circuit: 0.91 N.m Philips No 2 screwdriver Communication: 0.50.6 N.m Philips no 1 screwdriver Secondary circuit: 0.50.6 N.m Philips no 1 screwdriver

Wire Stripping Length	Current circuit: 3.68 mm Voltage circuit: 7 mm Control circuit: 7 mm Communication: 7 mm 7 mm	
Standards	IEC 61010-1:ed. 3 UL 61010-1:ed. 3	
Product Certifications	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1 CULus conforming to CSA C22.2 No 61010-1 C-Tick	
Width	96 mm	
Depth	13 mm outside: 49 mm panel:	
Height	96 mm	
Net Weight	300 g	

Environment

Electromagnetic Compatibility	Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Emission tests conforming to FCC part 15 Class A Emission tests conforming to FCC part 15 Subpart C Emission tests conforming to FCC part 15 Subpart E
Overvoltage Category	III
Ip Degree Of Protection	IP51 front: conforming to IEC 60529 IP30 body: conforming to IEC 60529
Relative Humidity	595 % at 50 °C
Pollution Degree	2
Ambient Air Temperature For Operation	-1060 °C
Ambient Air Temperature For Storage	-2070 °C
Operating Altitude	<= 2000 m
Service Life	7 year(s)

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9 cm
Package 1 Width	11.8 cm
Package 1 Length	12.4 cm
Package 1 Weight	360 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	18
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm

Package 2 Weight

4.86 kg

Contractual warranty

Warranty

CONZERV EM6438H DUAL P&E RS485 CL 0.5



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information