# **Product datasheet**

Specifications





# EasyLogic panel mount meter, class 0.5, RS485, LED

METSEPM1125HCL05RD

### Main

main	
Range	EasyLogic
Product name	EasyLogic PM11XXH RS
Device short name	PM1125H
Product or component type	Energy meter

### Complementary

Power quality analysis	total harmonic distortion
Device application	Energy monitoring
Type of measurement	Current Voltage Frequency Power factor Phase angle RPM Peak demand power Harmonic distorsion (I THD & U THD) Active power Active energy
Metering type	Average current lavg Phase currents Active power P, P1, P2, P3 Active, reactive, apparent energy (signed, four quadrant) Rotation speed Average voltage Vavg Calculated neutral current Unbalance current Apparent power S, S1, S2, S3 Unbalance voltage Frequency Voltage U21, U32, U13, V1, V2, V3 Demand power P, Q, S Reactive power Q, Q1, Q2, Q3 Power factor and displacement PF (signed, four quadrant) Phase current I1, I2, I3 RMS
Counter functions	ON hour counting ON-load hour counting Power interruption
[Us] rated supply voltage	48277 V AC 4565 Hz 48277 V DC
Network frequency	60 Hz 50 Hz
[In] rated current	1 A 5 A

type of network	3P	
	2P + N 1P + N	
	3P + N	
	2P	
Maximum power consumption in VA	4 VA at 240 V between phase and neutral	
Maximum power consumption in W	2 W at 240 V	
Display type	8 segments LED	
Display colour	Red	
Messages display capacity	3 fields of 4 characters	
Display digits	12 digit(s) - 14.2 mm in height	
communication of data	Reading of measurements	
	All counters	
	Revolution speed Last cleared log	
	Instantaneous and demand values	
Tamperproof of settings	Protected by access code	
Sampling rate	32 samples/cycle	
Measurement current	56000 mA	
Signal	Voltage (impedance 5 MOhm)4 x Current 0.00510 A (impedance 0.3 MOhm)6 x	
Measurement voltage	46277 V AC 5060 Hz between phase and neutral	
-	80480 V AC 5060 Hz between phases	
	277999000 V AC 5060 Hz with external VT	
Frequency measurement range	4565 Hz	
Measurement accuracy	Current +/- 0.5 %	
	Voltage +/- 0.5 %	
	Frequency +/- 0.05 % Power factor +/- 0.01	
	Reactive power +/- 1 %	
	Active power +/- 1 %	
	Apparent power +/- 0.5 %	
	Active energy +/- 0.5 %	
	Reactive energy +/- 2 %	
	Apparent energy +/- 0.5 % Harmonic distorsion (I THD & U THD) +/- 5 %	
Accuracy class	Class 0.5 active energy conforming to IEC 62053-21 Class 0.5 reactive energy conforming to IEC 62053-24	
Demand intervals	1 s	
Local signalling	Green LED: activity Red LED: output signal 19999000 pulse/ k_h (kWh, kVAh, kVARh)	
Communication port protocol	Modbus at 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps even/odd or none - 2 wires, insulation 2500 V	
Communication port support	Screw connector: RS485	
Data recording	Energy consumption logs	
Material	Polycarbonate	
Flame retardance	V-0 conforming to UL 94	
Mounting mode	Flush-mounted	
Mounting support	Framework	
Provided equipment	Installation guide	
Installation category	11	
Type of installation	Indoor installation	

Measurement category	Category III 480 V	
Electrical insulation class	Class II	
Connections - terminals	Current circuit: screw clamp terminals (bottom) 2.083.31 mm <sup>2</sup> cable(s) Voltage circuit: screw clamp terminals (top) 0.823.31 mm <sup>2</sup> cable(s) Control circuit: screw clamp terminals (top) 0.823.31 mm <sup>2</sup> cable(s) Communication: screw clamp terminals (bottom) 0.333.31 mm <sup>2</sup> cable(s)	
Tightening torque	Current circuit: 0.91 N.m Philips No 2 screwdriver Voltage circuit: 0.91 N.m Philips No 2 screwdriver Control circuit: 0.91 N.m Philips No 2 screwdriver Communication: 0.50.6 N.m Philips no 1 screwdriver	
Wire stripping length	Current circuit: 3.68 mm Voltage circuit: 7 mm Control circuit: 7 mm 7 mm	
Standards	IEC 61010-1:ed. 3 UL 61010-1:ed. 3	
Product certifications	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1 CULus conforming to CSA C22.2 No 61010-1 C-Tick	
Width	96 mm	
Depth	Outside : 13 mm Panel : 49 mm	
Height	96 mm	
Net weight	300 g	

## Environment

Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC	
Radiated radio-frequency electromagnetic field immunity test conforming to IEC	
61000-4-3	
Electrical fast transient/burst immunity test conforming to IEC 61000-4-4	
Surge immunity test conforming to IEC 61000-4-5	
Conducted RF disturbances conforming to IEC 61000-4-6	
Magnetic field at power frequency conforming to IEC 61000-4-8	
Voltage dips and interruptions immunity test conforming to IEC 61000-4-11	
Emission tests conforming to FCC part 15 class A	
Emission tests conforming to FCC part 15 Subpart C	
Emission tests conforming to FCC part 15 Subpart E	
III	
IP51 front: conforming to IEC 60529	
IP30 body: conforming to IEC 60529	
595 % at 50 °C	
2	
-1060 °C	
-2070 °C	
<= 2000 m	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.88 cm
Package 1 Width	9.6 cm

Package 1 Length	9.6 cm
Package 1 Weight	350.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	6300.0 g

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance



Rohs Exemption Information

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information