Product datasheet

Specifications





EasyLogic PM2230, Power & Energy meter, up to 31stH, LCD, RS485, class 0.5S

METSEPM2230D

Main

| wan | |
|---------------------------|------------------|
| Range | EasyLogic |
| Product Name | EasyLogic PM2200 |
| Device Short Name | PM2230 |
| Product Or Component Type | Power meter |

Complementary

| Complementary | |
|-----------------------------|---|
| Device Application | Power monitoring Sub billing |
| Power Quality Analysis | total harmonic distortion |
| | up to the 31st harmonic |
| Type Of Measurement | Apparent power min/max, total |
| | Active and reactive power min/max, total |
| | Current min/max, avg |
| | Voltage min/max, avg |
| | Frequency min/max, avg |
| | Total current harmonic distortion THD (I) per phase |
| | Total voltage harmonic distortion THD (U) per phase |
| | Power factor min/max, avg |
| | Apparent energy total |
| | Active and reactive energy total |
| Metering Type | Active, reactive, apparent energy (signed, four quadrant) |
| | Active power P, P1, P2, P3 |
| | Current I, I1, I2, I3 |
| | Peak demand currents |
| | Apparent power S, S1, S2, S3 |
| | Calculated neutral current |
| | Unbalance current |
| | Reactive power Q, Q1, Q2, Q3 |
| | Demand power P, Q, S |
| | Peak demand power PM, QM, SM |
| | Voltage U, U21, U32, U13, V, V1, V2, V3 |
| Accuracy Class | Class 1 reactive energy conforming to IEC 62053-24 |
| | Class 0.5S active energy conforming to IEC 62053-22 |
| | Class 5 harmonic distorsion (I THD & U THD) |
| Measurement Accuracy | Apparent power +/- 0.5 % |
| | Active energy +/- 0.5 % |
| | Reactive energy +/- 1 % |
| | Active power +/- 0.5 % |
| | Voltage +/- 0.5 % |
| | Power factor +/- 0.01 |
| | Current +/- 0.5 % |
| | Frequency +/- 0.05 % |
| Measurement Current | 56000 mA |
| Measurement Voltage | 35480 V AC 50/60 Hz between phases |
| | 20277 V AC 50/60 Hz between phase and neutral |
| | 480999000 V AC 50/60 Hz with external VT |
| Frequency Measurement Range | 4565 Hz |
| Frequency Measurement Range | 480999000 V AC 50/60 Hz with external VT |

| [Us] Rated Supply Voltage | 80277 V AC 4565 Hz +/- 10 % 100277 V DC +/- 10 % | |
|------------------------------------|---|--|
| Network Frequency | 50 Hz 60 Hz | |
| Ride-Through Time | 50 ms 120 V AC typical 50 ms 230 V AC typical 50 ms 125 V DC typical | |
| [In] Rated Current | 5 A 1 A | |
| Maximum Power Consumption In Va | 8 VA at 277 V AC | |
| Maximum Power Consumption In W | 3.3 W (power lines (AC)) 3.3 W at 277 V (power lines (DC)) | |
| Input Impedance | Current (impedance <= 0.3 mOhm) Voltage (impedance > 5 MOhm) | |
| Tamperproof Of Settings | Protected by access code | |
| Display Type | Backlit LCD | |
| Display Colour | Monochrome | |
| Display Resolution | 128 x 128 pixels | |
| Demand Intervals | Configurable from 1 to 60 min | |
| Information Displayed | Demand current (past value) Demand current (present value) Demand power (past value) Demand power (present value) Voltage Current Frequency Energy consumption Harmonic distortion Power factor Active power Apparent power Reactive power Unbalanced in % Harmonic amplitude | |
| Control Type | 4 x button | |
| Local Signalling | Red LED: output signal 19999000 pulse/ k_h (kWh, kVAh, kVARh) Green LED: module operation and integrated communication | |
| Number Of Inputs | 0 | |
| Number Of Outputs | 0 | |
| Communication Port Protocol | Modbus RTU at 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps even/odd or none - 2 wires, insulation 2500 V | |
| Communication Port Support | Screw terminal block: RS485 | |
| Data Recording | Power logs Min/max for 8 parameters Energy consumption logs Time stamping | |
| Function Available | Real time clock | |
| Sampling Rate | 64 samples/cycle | |
| Cybersecurity | Enable/disable communication ports | |
| Communication Service | Remote monitoring | |

| Language | Portuguese |
|---------------------------------------|--|
| 0 0 | German |
| | Chinese |
| | |
| | English |
| | Spanish |
| | French |
| | Russian |
| | |
| Product Certifications | CE conforming to IEC 61010-1 |
| | CULus conforming to UL 61010-1 |
| | |
| | CULus conforming to CSA C22.2 No 61010-1 |
| | RCM |
| | EAC |
| | C-Tick |
| | 0 Hok |
| Mounting Mode | Clip-on |
| | · |
| Mounting Position | Vertical |
| | |
| Mounting Support | Framework |
| | |
| Provided Equipment | 1 x installation guide |
| | |
| Measurement Category | Category III 480 V |
| | Category II 480600 V |
| | |
| Electrical Insulation Class | Double insulation |
| | Class II |
| | |
| Flame Retardance | V-0 conforming to UL 94 |
| | |
| Connections - Terminals | Current transformer: screw connection (bottom) 6 |
| | Voltage inputs: screw connection (top) 4 |
| | Voltage inputs. Sciew connection (top) 4 |
| Material | Polycarbonate |
| | |
| Width | 96 mm |
| | |
| Depth | 76.09 mm total: |
| | 61.64 mm embedded: |
| | |
| Height | 96 mm |
| · · · · · · · · · · · · · · · · · · · | |
| | |
| Net Weight | 300 g |
| Net Weight | 300 g |
| Net Weight Targeted Country | 300 g |

Environment

| Service Life | 7 year(s) |
|--|---|
| Ip Degree Of Protection | IP54 front: conforming to IEC 60529 IP30 body: conforming to IEC 60529 |
| Relative Humidity | 595 % at 50 °C |
| Pollution Degree | 2 |
| Ambient Air Temperature For Operation | -1060 °C |
| Ambient Air Temperature For Storage | -2570 °C |
| Operating Altitude | <= 2000 m |
| Electromagnetic Compatibility | Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Emission tests conforming to FCC part 15 class A |
| Overvoltage Category | III |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|--------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 7.2 cm |
| Package 1 Width | 9.6 cm |
| Package 1 Length | 9.6 cm |
| Package 1 Weight | 0.5 kg |

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|-------------------------------|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |