Product datasheet

Specifications

EasyLogic PM2X30 - I/O Module - Analogue - 2 inputs + 2 outputs

METSEPM2KANLGIO22D

Main

Range	EasyLogic
Device Short Name	PM2K2AIAO
Product Or Component Type	I/O module
Device Application	Optional expansion module
Range Compatibility	EasyLogic EasyLogic PM2100 PM2130 EasyLogic EasyLogic PM2200 PM2230

Complementary

[Ui] Rated Insulation Voltage	2500 V
Number Of Outputs	2 analog, 4...20 mA
Output Voltage	12 V AC
Analogue Input Type	Analog input (impedance <= 300 Ohm)
Number Of Inputs	2 analog 4...20 mA
Input Voltage	12...30 V AC
Analogue Output Type	Analog output, impedance <600 Ohm
Width	90.5 mm
Depth	14.6 mm
Height	53 mm
Net Weight	50 g
Targeted Country	India

Environment

Ambient Air Temperature For Operation	-10…60 °C
Ambient Air Temperature For Storage	-25…70 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	9.6 cm
Package 1 Length	9.6 cm
Package 1 Weight	0.2 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency

RoHS/REACh

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information