



Miniature circuit-breaker, Miluz Lara, 20A, C-curve, 1 module, white

MLMM201P_WH

Main

Range	Miluz
Device application	Distribution
product or component type	Miniature circuit-breaker
Device presentation	Basic element with central cover plate
poles description	1P
Rated current	20 A at 240 V AC
Number of modules	1 module
Fixing mode	Snap-fitted

Complementary

Connections - terminals	Screw terminals
Clamping connection capacity	4 mm²
Trip unit technology	Thermal-magnetic
breaking capacity	3 kA
Material	Polycarbonate and polyamide
Standards	IEC 60898
ambient air temperature for operation	-545 °C
Depth	59.18 mm
Width	22.2 mm
Height	56 mm
Curve code	С
Relative humidity	095 %

Environment

IP degree of protection IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.918 cm
Package 1 Width	2.22 cm
Package 1 Length	5.6 cm

Package 1 Weight	67 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	6.45 cm
Package 2 Width	6.2 cm
Package 2 Length	26.3 cm
Package 2 Weight	740.2 g



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Image of product / Alternate images

Alternative













