



# Power supply, Spacelogic KNX, REG-K/640 mA, white

MTN6513-1202

#### Main

Range of product	SpaceLogic KNX	
Product or component type	Power supply	
Bus type	KNX	
Topology	TP256	
Provided equipment	Line choke	
Colour	White	

## **Complementary**

total number of 18 mm modules	4	
Mounting support	DIN rail	
Rated voltage	180264 V AC 5060 Hz	
Power consumption in W	2.9 W	
Maximum short-circuit current	uit current 1.5 A	
Maximum output current	640 mA	
Output voltage	30 V DC	
Power supply type	type SELV	
Local signalling	g LED	
Connections - terminals	0.54 mm² screw terminal for solid cable 0.54 mm² screw terminal for stranded cable 0.52.5 mm² screw terminal for stranded with sleeve cable	
Height	90 mm	
Width	72 mm	
Depth	65 mm	

## **Environment**

Ambient air temperature for operation	-545 °C	
Ambient air temperature for storage	-2570 °C	
Relative humidity	93 % non-condensing	
Operating altitude	2000 m	
Directives	89/336/EEC - electromagnetic compatibility	

#### **Packing Units**

Unit Type of Package 1 PCE

Number of Units in Package 1	1
Package 1 Height	8.000 cm
Package 1 Width	12.400 cm
Package 1 Length	16.000 cm
Package 1 Weight	347.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	28
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	10.774 kg
Unit Type of Package 3	P12
Number of Units in Package 3	224
Package 3 Height	75.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	98.192 kg



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>②</b>	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

Image of product / Alternate images

#### **Alternative**













