Product datasheet

Specifications





KNX DALI-Gateway Basic REG-K/ 1/16/64

MTN6725-0003

Main

Range of product	KNX	
Product or component type	KNX DALI gateway	
Bus type	KNX	
Function available	Updateable software	

Complementary

total number of 18 mm modules	4	
Mounting support	DIN rail	
[Ue] rated operational voltage	100240 V	
Network frequency	50/60 Hz	
Communication port protocol	DALI	
local signalling	LED	

Environment

IP	degree o	f pro	tection	IP20
----	----------	-------	---------	------

Packing Units

J		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.200 cm	
Package 1 Width	13.300 cm	
Package 1 Length	15.800 cm	
Package 1 Weight	208.000 g	
Unit Type of Package 2	S04	
Number of Units in Package 2	28	
Package 2 Height	30.000 cm	
Package 2 Width	40.000 cm	
Package 2 Length	60.000 cm	
Package 2 Weight	6.384 kg	

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information