
# **Product datasheet**

Specifications





# KNX DALI-Gateway Basic REG-K/2/16/64

MTN6725-0004

#### Main

Range of product	KNX
Product or component type	KNX DALI gateway
Bus type	KNX
Function available	Undateable software

## Complementary

total number of 18 mm modules	4
Mounting support	DIN rail
[Ue] rated operational voltage	100240 V
Network frequency	50/60 Hz
Communication port protocol	DALI
local signalling	LED

#### **Environment**

IP degree of protection IP20

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.200 cm
Package 1 Width	13.300 cm
Package 1 Length	15.900 cm
Package 1 Weight	228.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	28
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	6.984 kg



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

# Well-being performance

✓ Toxic Heavy Metal Free
 ✓ Mercury Free
 ✓ Rohs Exemption Information

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information