# **Product datasheet**

Specification





## Circuit breaker, EasyPact MVS, 4 Poles, 800A, 50kA, EDO, ETV2, drawout, electrical

MVS08N4NW2V

#### Main

| Range                          | EasyPact                                    |
|--------------------------------|---|
| Product name                   | MVS08N                                      |
| Device short name              | MVS08N                                      |
| Product or component type      | Circuit breaker                             |
| Device application             | Distribution                                |
| poles description              | 4P  |
| Protected poles description    | 4P 4d                                       |
| Neutral position               | Left  |
| [In] rated current             | 800 A at 40 °C                              |
| network type                   | AC  |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Breaking capacity code         | N   |
| Suitability for isolation      | Yes conforming to IEC 60947-2               |
| Utilisation category           | Category B                                  |
| Trip unit name                 | ETV2I                                       |
| Trip unit technology           | Electronic                                  |
| Trip unit rating               | 800 A                                       |

## Complementary

| Network frequency                      | 50/60 Hz  |
|--|---|
| Control type                           | Electrically operated   |
| Mounting mode                          | Drawout   |
| Mounting support                       | Rail<br>Base plate  |
| Connection position                    | Horizontal<br>Vertical  |
| Location of connection                 | Rear  |
| [Ui] rated insulation voltage          | 1000 V AC 50/60 Hz conforming to IEC 60947-2                  |
| [Uimp] rated impulse withstand voltage | 12 kV conforming to IEC 60947-2                               |
| circuit breaker CT rating              | 800 A   |
| Breaking capacity                      | 50 kA Icu at 220440 V AC 50/60 Hz conforming to IEC 60947-2   |
| [lcs] rated service breaking capacity  | 50 kA (Ics) at 220440 V AC 50/60 Hz conforming to IEC 60947-2 |

| Mechanical durability                     | 20000 cycles (with maintenance) conforming to IEC 60947-2 10000 cycles (without maintenance) conforming to IEC 60947-2  |
|---|---|
| Electrical durability                     | Category B: 6000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 Category B: 4000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2               |
| Connection pitch                          | 115 mm without spreader   |
| Contact position indicator                | Yes   |
| [Icm] rated short-circuit making capacity | 105 kA (Icm) at 220440 V AC 50/60 Hz conforming to IEC 60947-2  |
| [lcw] rated short-time withstand current  | 50 kA (1 s) at 220440 V AC 50/60 Hz conforming to IEC 60947-2<br>42 kA (1 s) at 690 V AC 50/60 Hz conforming to IEC 60947-2<br>25 kA (3 s) at 440/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Neutral protection setting                | Without protection (3D)<br>0.5 x lr (3D + N/2)<br>1 x lr (4D)   |
| Trip unit protection functions            | Ц   |
| Protection type                           | Instantaneous short-circuit protection Overload protection (long time)  |
| Fault indication                          | Internal fault<br>Short-circuit<br>Overload   |
| Long time pick-up adjustment type Ir      | Adjustable 9 settings   |
| Long time pick-up adjustment range        | 0.41 x ln   |
| Long time delay adjustment type           | Adjustable 9 settings   |
| [tr] long-time delay adjustment range     | 0.524 s at 6 x Ir   |
| thermal memory                            | 20 minutes before and after tripping  |
| Instantaneous pick-up adjustment type li  | Adjustable 9 settings   |
| instantaneous pick-up adjustment range    | 1.510 x lr  |
| Zone selective interlocking ZSI           | With  |
| Display type                              | Digital display   |
| type of measurement                       | Voltage   |
| Current sensor rating range               | 400/2000 A  |
| Maximum breaking time                     | 25 ms   |
| Maximum closing response time             | 70 ms   |
| Height                                    | 439 mm  |
| Width                                     | 556 mm  |
| Depth                                     | 395 mm  |
| Net weight                                | 85 kg   |
|   |   |

## **Environment**

| Standards               | IEC 60947-2                 |
|-------------------------|-----------------------------|
| Product certifications  | IEC<br>CCS<br>CCC<br>GOST   |
| Pollution degree        | 4 conforming to IEC 60664-1 |
| IP degree of protection | IP40                        |

| Ambient air temperature for operation | -570 °C   |
|---------------------------------------|---|
| Ambient air temperature for storage   | -4085 °C without control unit<br>-2585 °C with control unit |

# **Packing Units**

| Unit Type of Package 1       | PCE     |
|------------------------------|---------|
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 42.0 cm |
| Package 1 Width              | 35.0 cm |
| Package 1 Length             | 50.0 cm |
| Package 1 Weight             | 38.0 kg |

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes


#### **Certifications & Standards**


| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | End of Life Information   |

## **Product datasheet**

#### MVS08N4NW2V

#### **Dimensions Drawings**







## **Product datasheet**

#### MVS08N4NW2V

#### Assembly





#### MVS08N4NW2V

#### Performance Curves

