# **Product datasheet**

Specifications





# EP MVS 1000A 50kA 3P MF W/O PROT fixed manual switch disconnector

MVS10N3MF0D

#### Main

Range of product	EasyPact MVS
Range	EasyPact
Product name	MVS10NA
Device short name	MVS10NA
Product or component type	Switch disconnector
Device application	Distribution
poles description	3P
network type	AC
Suitability for isolation	Yes conforming to IEC 60947-2
Utilisation category	AC-23A

### Complementary

Network frequency	50/60 Hz	
Control type	Manually operated	
Mounting mode	Fixed	
Mounting support	Rail Base plate	
Connection position	Vertical Horizontal	
Location of connection	Rear	
[le] rated operational current	AC-23A: 1000 A AC 50/60 Hz 690 V	
Rated duty	Continuous	
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-3	
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-3	
[Icw] rated short-time withstand current	50 kA during 1 s conforming to IEC 60947-3 at -5…70 °C 25 kA during 3 s conforming to IEC 60947-3 at -5…70 °C	
[lcm] rated short-circuit making capacity	105 kA AC at 50/60 Hz	
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-3	
Contact position indicator	Yes	
Mechanical durability	20000 cycles with maintenance conforming to IEC 60947-3	

10000 cycles without maintenance conforming to IEC 60947-3

Excluding VAT, FCA Jabal Ali & are subject to change - check with your local distributor.

Electrical durability	AC-23A: 6000000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-3 AC-23A: 4000000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-3
Connection pitch	115 mm without spreader
Height	352 mm
Width	422 mm
Depth	297 mm
Net weight	40 kg

#### Environment

Standards	IEC 60947-3
Product certifications	CCS CCC GOST IEC
IP degree of protection	IP40
Pollution degree	4 conforming to IEC 60664-1
Ambient air temperature for operation	-570 °C
Ambient air temperature for storage	-4085 °C without control unit

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	42.0 cm
Package 1 Width	35.0 cm
Package 1 Length	50.0 cm
Package 1 Weight	38.0 kg

### **Contractual warranty**

Warranty

18 months

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance


Mercury Free
Rohs Exemption Information Yes
Pvc Free


#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	

**Product datasheet** 

**Dimensions Drawings** 





Assembly

