# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# Circuit breaker, Stab-Lok, 60A, 2 pole, 120VAC, 10kA, plug in mount

NA260

### Main

Range of product	Stab-lok
Product or component type	Miniature circuit-breaker
[In] rated current	60 A
[Ue] rated operational voltage	120/240 V AC
Poles description	2P
Breaking capacity	10 kA

## Complementary

Mounting mode	Plug-in	
Electrical connection	Screw connector	
AWG gauge	AWG 14AWG 2 copper	

### **Environment**

Product certifications CSA

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.00 in (5.08 cm)
Package 1 Width	3.00 in (7.62 cm)
Package 1 Length	3.50 in (8.89 cm)
Package 1 Weight	10.400 oz (294.835 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	15
Package 2 Height	3.70 in (9.398 cm)
Package 2 Width	10.90 in (27.686 cm)
Package 2 Length	10.50 in (26.67 cm)
Package 2 Weight	10.490 lb(US) (4.758 kg)

# **Environmental Data**

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Carbon footprint (kg CO2 eq, Total Life cycle)	250	

### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	770cc9ea-53d2-4d3d- a57a-062b35abd847
China RoHS Regulation	China RoHS declaration

# **Use Again**

○ Repack and remanufacture	
Take-back	No