

# Product data sheet

Specifications



Circuit breaker, Stab-Lok, 60A, 3 pole, 240VAC, 10kA, plug in mount

NA3P60

## Main

Range of product	Stab-lok
Product or component type	Miniature circuit-breaker
[In] rated current	60 A
[Ue] rated operational voltage	240 V AC
Poles description	3P
Breaking capacity	10 kA

## Complementary

Mounting mode	Plug-in
Electrical connection	Screw connector
AWG gauge	AWG 14...AWG 1/0 copper

## Environment

Product certifications	CSA
------------------------	-----

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.00 in (7.62 cm)
Package 1 Width	3.20 in (8.128 cm)
Package 1 Length	4.00 in (10.16 cm)
Package 1 Weight	20.000 oz (566.991 g)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications




## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.


[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	770cc9ea-53d2-4d3d-a57a-062b35abd847
China RoHS Regulation	<a href="#">China RoHS declaration</a>

### Use Again

 <b>Repack and remanufacture</b>	
Take-back	No