

Circuit breaker, Stab-Lok, 40A, 2 pole, 120/240VAC, 10kA, bolt on mount

NB240

Main

Range of product	Stab-lok
Product or component type	Miniature circuit-breaker

Complementary

•	
[In] rated current	40 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Bolt-on
Poles description	2P
Breaking capacity	10 kA
Electrical connection	Screw connector
AWG gauge	AWG 14AWG 2 aluminum/copper AWG 4AWG 2/0 aluminum/copper

Environment

Product certifications CSA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.00 in (5.08 cm)
Package 1 Width	3.00 in (7.62 cm)
Package 1 Length	3.50 in (8.89 cm)
Package 1 Weight	10.400 oz (294.835 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	30
Package 2 Height	6.80 in (17.272 cm)
Package 2 Width	10.50 in (26.67 cm)
Package 2 Length	10.90 in (27.686 cm)
Package 2 Weight	20.90 lb(US) (9.48 kg)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Carbon footprint (kg CO2 eq, Total Life cycle)	250	

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	770cc9ea-53d2-4d3d- a57a-062b35abd847
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Take-back	No