Product data sheet

Specifications

Circuit breaker, Stab-Lok, 15A, 3 pole, 240VAC, 10kA, bolt on mount

NB3P15

Main

Range of product	Stab-lok
Product or component type	Miniature circuit-breaker

Complementary

[In] rated current	15 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Bolt-on
Poles description	3P
Breaking capacity	10 kA
Electrical connection	Screw connector
AWG gauge	AWG 14...AWG 1/0 aluminum/copper

Environment

Product certifications	CSA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.00 in (7.62 cm)
Package 1 Width	3.20 in (8.128 cm)
Package 1 Length	4.00 in (10.16 cm)
Package 1 Weight	19.680 oz (557.919 g)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant with Exemptions**
SCIP Number	**770cc9ea-53d2-4d3d-a57a-062b35abd847**
China RoHS Regulation	**China RoHS declaration**

Use Again

Repack and remanufacture

Take-back	**No**