

NRT3-U11000CLAC

Strong points

- Simple to install
- High protection and availability
- Certified performance
- Easy to use
- Extended and flexible back-up time

General characteristics

- Rail kit.
- Embedded dry-contact interface (5000- 11000 VA).
- Input mains switch breaker (5000-11000 VA).
- Connection for battery extension modules.
- Port for parallel operation (5000-11000 VA).
- Power off the UPS remotely.
- Internal temperature sensor.

Compliance with standards

- IEC 62040-1
- IEC 62040-2
- IEC 62040-3
- AS 62040.1.1
- AS 62040.1.2
- AS 62040.2
- RCM (E2376)

Access to resources (ex: manuals)

Complete and professional, NETYS RT is a single-phase rack-tower UPS ensuring protection and availability of IT infrastructure that meet both requirements of power reliability and installation flexibility.

Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149
Commerce	
Effective date	2021-04-01
Obsolescence date	2025-04-01
Country of origin	IT
Weight	17
Logistics	
Customs number	8504409590
Technical Characteristics	
Depth	565
Height	89
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	440
Sn	11
Pn	10
Conf	C1
Input voltage	230
Rate (min)	11
Rate (max)	11
Configuration	UPS Single Unit(s) with Bypass

2024-10-24 14:48:25