

NRT3-U7000CLAC

Strong points

- Simple to install
- High protection and availability
- Certified performance
- Easy to use
- Extended and flexible back-up time

General characteristics

- Rail kit.

- Embedded dry-contact interface (5000- 11000 VA).Input mains switch breaker
- (5000-11000 VA).
- Connection for battery extension modules.
- Port for parallel operation
- (5000-11000 VA).
- Power off the UPS remotely.
- Internal temperature sensor.

Compliance with standards

- IEC 62040-1
- IEC 62040-2
- IEC 62040-3
- AS 62040.1.1
- AS 62040.1.2
- AS 62040.2
- RCM (E2376)

Access to resources (ex: manuals)

Complete and professional, NETYS RT is a single-phase rack-tower UPS ensuring protection and availability of IT infrastructure that meet both requirements of power reliability and installation flexibility.

Classification

UNSPSC 39121011 ETIM Class EC000382 IGCC 4149 Commerce 2021-04-15 Effective date 2025-04-01 Country of origin IT Weight 12 Logistics 2025-04-01 Customs number 8504409590 Technical Characteristics 200 Depth 430 Height 89 In/out 1/1 Output voltage 230 Rated frequency 50/50 Width 440 Sn 7 Pn 6 Conf C1 Input voltage 230 Rate (min) 7	Classification	
IGCC4149IGCC4149CommerceEffective date2021-04-15Obsolescence date2025-04-01Country of originITWeight12LogisticsEcustoms numberCustoms number8504409590Technical CharacteristicsDepth430Height89In/out1/1Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	UNSPSC	39121011
CommerceEffective date2021-04-15Obsolescence date2025-04-01Country of originITWeight12Logistics8504409590Customs number8504409590Technical CharacteristicsDepth430Height89In/out1/1Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	ETIM Class	EC000382
Effective date2021-04-15Obsolescence date2025-04-01Country of originITWeight12Logistics8504409590Customs number8504409590Technical CharacteristicsDepth430Height89In/out1/1Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	IGCC	4149
ActionActionObsolescence date2025-04-01Country of originITWeight12Logistics8504409590Customs number8504409590Technical CharacteristicsDepth430Height89In/out1/1Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Commerce	
Country of originITWeight12Logistics8504409590Customs number8504409590Technical CharacteristicsDepth430Height89In/out1/1Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Effective date	2021-04-15
Weight12Logistics8504409590Customs number8504409590Technical Characteristics9Depth430Height89In/out1/1Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Obsolescence date	2025-04-01
LogisticsCustoms number8504409590Technical CharacteristicsDepth430Height89In/out1/1Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Country of origin	IT
Customs number8504409590Technical CharacteristicsDepth430Height89In/out1/1Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Weight	12
Technical CharacteristicsDepth430Height89In/out1/1Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Logistics	
Depth430Height89In/out1/1Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Customs number	8504409590
Height89In/out1/1Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Technical Characteristics	5
In/out1/1Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Depth	430
Output voltage230Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Height	89
Rated frequency50/50Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	In/out	1/1
Width440Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Output voltage	230
Sn7Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Rated frequency	50/50
Pn6ConfC1Input voltage230Rate (min)7Rate (max)7	Width	440
ConfC1Input voltage230Rate (min)7Rate (max)7	Sn	7
Input voltage230Rate (min)7Rate (max)7	Pn	6
Rate (min)7Rate (max)7	Conf	C1
Rate (max) 7	Input voltage	230
	Rate (min)	7
	Rate (max)	7
Configuration UPS Single Unit(s) with Bypass	Configuration	UPS Single Unit(s) with Bypass