

**Circuit-breaker, 3p, 32A**

**Part no.** **NZMN1-A32**  
**281233**  
**EL Number** **4358981**  
**(Norway)**

**General specifications**

|                      |  |
|----------------------|--|
| Product name         | Eaton Moeller series NZM molded case circuit breaker thermo-magnetic |
| Part no.             | NZMN1-A32  |
| EAN                  | 4015082812331  |
| Product Length/Depth | 88 millimetre  |
| Product height       | 145 millimetre   |
| Product width        | 90 millimetre  |
| Product weight       | 1.06 kilogram  |
| Compliances          | RoHS conform   |
| Certifications       | IEC<br>IEC/EN 60947  |
| Product Tradename    | NZM  |
| Product Type         | Molded case circuit breaker  |
| Product Sub Type     | Thermo-magnetic  |

**Delivery program**

|                            |  |
|----------------------------|--|
| Application                | Use in unearthed supply systems at 690 V   |
| Type                       | Circuit breaker  |
| Circuit breaker frame type | NZM1   |
| Number of poles            | Three-pole   |
| Amperage Rating            | 32 A   |
| Release system             | Thermomagnetic release   |
| Features                   | Protection unit  |
| Special features           | Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I <sub>cn</sub> )<br>Rated current = rated uninterrupted current: 32 A<br>Terminal capacity hint: Up to 95 mm <sup>2</sup> can be connected depending on the cable manufacturer. |

**Technical Data - Electrical**

|   |               |
|---|---------------|
| Voltage rating  | 690 V - 690 V |
| Voltage rating (DC)   | 450 V DC      |
| Rated insulation voltage (U <sub>i</sub> )  | 690 V AC      |
| Rated impulse withstand voltage (U <sub>imp</sub> ) at auxiliary contacts                   | 6000 V        |
| Rated impulse withstand voltage (U <sub>imp</sub> ) at main contacts                        | 6000 V        |
| Instantaneous current setting (I <sub>i</sub> ) - min                                       | 350 A         |
| Instantaneous current setting (I <sub>i</sub> ) - max                                       | 350 A         |
| Overload current setting (I <sub>r</sub> ) - min  | 25 A          |
| Overload current setting (I <sub>r</sub> ) - max  | 32 A          |
| Short delay current setting (I <sub>sd</sub> ) - min  | 0 A           |
| Short delay current setting (I <sub>sd</sub> ) - max  | 0 A           |
| Short-circuit release non-delayed setting - min   | 350 A         |
| Short-circuit release non-delayed setting - max   | 350 A         |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 230 V, 50/60 Hz     | 85 kA         |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 400/415 V, 50/60 Hz | 50 kA         |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 440 V, 50/60 Hz     | 35 kA         |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 525 V, 50/60 Hz     | 10 kA         |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 690 V, 50/60 Hz     | 7.5 kA        |
| Rated short-circuit making capacity I <sub>cm</sub> at 240 V, 50/60 Hz                      | 187 kA        |
| Rated short-circuit making capacity I <sub>cm</sub> at 400/415 V, 50/60 Hz                  | 105 kA        |
| Rated short-circuit making capacity I <sub>cm</sub> at 440 V, 50/60 Hz                      | 74 kA         |

|   |  |   |
|---|--|---|
| Rated short-circuit making capacity Icm at 525 V, 50/60 Hz      |  | 40 kA   |
| Rated short-circuit making capacity Icm at 690 V, 50/60 Hz      |  | 17 kA   |
| Short-circuit total breaktime                                   |  | < 10 ms   |
| Electrical connection type of main circuit                      |  | Frame clamp   |
| Isolation   |  | 300 V AC (between the auxiliary contacts)<br>500 V AC (between auxiliary contacts and main contacts)  |
| Number of operations per hour - max                             |  | 120   |
| Handle type   |  | Rocker lever  |
| Utilization category  |  | A (IEC/EN 60947-2)  |
| Overvoltage category  |  | III   |
| Pollution degree  |  | 3   |
| Lifespan, electrical  |  | 7500 operations at 690 V AC-1<br>10000 operations at 415 V AC-1<br>10000 operations at 400 V AC-1   |
| Direction of incoming supply                                    |  | As required   |
| <b>Technical Data - Mechanical</b>                              |  |   |
| Mounting Method   |  | DIN rail (top hat rail) mounting optional<br>Built-in device fixed built-in technique<br>Fixed  |
| Degree of protection  |  | IP20<br>IP20 (basic degree of protection, in the operating controls area)   |
| Degree of protection (IP), front side                           |  | IP40 (with insulating surround)<br>IP66 (with door coupling rotary handle)  |
| Degree of protection (terminations)                             |  | IP00 (terminations, phase isolator and strip terminal)<br>IP10 (tunnel terminal)  |
| Protection against direct contact                               |  | Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110   |
| Shock resistance  |  | 20 g (half-sinusoidal shock 20 ms)  |
| Number of auxiliary contacts (change-over contacts)             |  | 0   |
| Number of auxiliary contacts (normally closed contacts)         |  | 0   |
| Number of auxiliary contacts (normally open contacts)           |  | 0   |
| Position of connection for main current circuit                 |  | Front side  |
| Climatic proofing   |  | Damp heat, cyclic, to IEC 60068-2-30<br>Damp heat, constant, to IEC 60068-2-78  |
| Special features  |  | Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)<br>Rated current = rated uninterrupted current: 32 A<br>Terminal capacity hint: Up to 95 mm² can be connected depending on the cable manufacturer. |
| Lifespan, mechanical  |  | 20000 operations  |
| <b>Technical Data - Mechanical - Terminals</b>                  |  |   |
| Standard terminals  |  | Box terminal  |
| Optional terminals  |  | Connection on rear. Screw terminal. Tunnel terminal   |
| Terminal capacity (control cable)                               |  | 0.75 mm² - 1.5 mm² (2x)<br>0.75 mm² - 2.5 mm² (1x)  |
| Terminal capacity (aluminum solid conductor/cable)              |  | 10 mm² - 16 mm² (2x) direct at switch rear-side connection<br>16 mm² (1x) at tunnel terminal<br>10 mm² - 16 mm² (1x) direct at switch rear-side connection  |
| Terminal capacity (aluminum stranded conductor/cable)           |  | 25 mm² - 95 mm² (1x) at tunnel terminal<br>25 mm² - 35 mm² (2x) direct at switch rear-side connection<br>25 mm² - 35 mm² (1x) direct at switch rear-side connection   |
| Terminal capacity (copper busbar)                               |  | Min. 12 mm x 5 mm direct at switch rear-side connection<br>Max. 16 mm x 5 mm direct at switch rear-side connection<br>M6 at rear-side screw connection  |
| Terminal capacity (copper solid conductor/cable)                |  | 10 mm² - 16 mm² (1x) direct at switch rear-side connection<br>6 mm² - 16 mm² (2x) at box terminal<br>6 mm² - 16 mm² (2x) direct at switch rear-side connection<br>16 mm² (1x) at tunnel terminal<br>10 mm² - 16 mm² (1x) at box terminal  |
| Terminal capacity (copper stranded conductor/cable)             |  | 25 mm² (2x) direct at switch rear-side connection<br>6 mm² - 25 mm² (2x) at box terminal<br>10 mm² - 70 mm² (1x) at box terminal<br>10 mm² - 70 mm² (1x) direct at switch rear-side connection<br>25 mm² - 95 mm² (1x) at 1-hole tunnel terminal  |
| Terminal capacity (copper strip)                                |  | Max. 9 segments of 9 mm x 0.8 mm at box terminal<br>Min. 2 segments of 9 mm x 0.8 mm at box terminal  |
| <b>Design verification as per IEC/EN 61439 - technical data</b> |  |   |

|  |  |  |
|--|--|--|
| Rated operational current for specified heat dissipation (In)                    |  | 32 A   |
| Equipment heat dissipation, current-dependent                                    |  | 9.31 W   |
| Ambient operating temperature - min  |  | -25 °C   |
| Ambient operating temperature - max  |  | 70 °C  |
| Ambient storage temperature - min  |  | 40 °C  |
| Ambient storage temperature - max  |  | 70 °C  |
| <b>Design verification as per IEC/EN 61439</b>                                   |  |  |
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components                           |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections                                |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>Additional information</b>  |  |  |
| Functions  |  | System and cable protection  |

## Technical data ETIM 9.0

|   |    |  |
|---|----|--|
| Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)   |    |  |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss13-27-37-04-09 [AJZ716018]) |    |  |
| Rated permanent current Iu  | A  | 32                                       |
| Rated voltage   | V  | 690 - 690                                |
| Rated short-circuit breaking capacity Icu at 400 V, 50 Hz   | kA | 50                                       |
| Overload release current setting  | A  | 25 - 32                                  |
| Adjustment range short-term delayed short-circuit release   | A  | 0 - 0                                    |
| Adjustment range undelayed short-circuit release  | A  | 350 - 350                                |
| Power loss  | W  | 9.3                                      |
| Device construction   |    | Built-in device fixed built-in technique |
| Integrated earth fault protection   |    | No                                       |
| Type of electrical connection of main circuit   |    | Frame clamp                              |
| Suitable for DIN rail (top hat rail) mounting   |    | No                                       |
| DIN rail (top hat rail) mounting optional   |    | Yes                                      |
| Number of auxiliary contacts as normally closed contact   |    | 0  |
| Number of auxiliary contacts as normally open contact   |    | 0  |
| Number of auxiliary contacts as change-over contact   |    | 0  |
| With switched-off indicator   |    | No                                       |
| With integrated under voltage release   |    | No                                       |
| Number of poles   |    | 3  |

|   |  |  |              |
|---|--|--|--------------|
| Position of connection for main current circuit |  |  | Front side   |
| Type of control element                         |  |  | Rocker lever |
| Complete device with protection unit            |  |  | Yes          |
| Motor drive integrated                          |  |  | No           |
| Motor drive optional                            |  |  | No           |
| Degree of protection (IP)                       |  |  | IP20         |