

# Socket-outlet, Livia, 2P+E with shutter, 13A, painted grey

P2010\_PG\_N

## Main

Range	Livia
Product or component type	Socket-outlet
Device application	Power supply
Colour tint	Grev

## Complementary

fixing mode	By screws By claws	
Device mounting	Flush	
Outlet poles configuration	2P + E with shutter	
Rated current	13 A at 220240 V AC 50/60 Hz	
Socket additional information	Shuttered	
Connections - terminals	Pillar terminal	
Material	PC (polycarbonate)	
surface treatment	Painted	
Surface finish	Matt	

## **Environment**

Ambient air temperature for operation	-560 °C
Ambient air temperature for storage	-560 °C
IP degree of protection	IP2X
Depth	45 mm
Width	45 mm
Height	54 mm

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6 cm
Package 1 Width	7 cm
Package 1 Length	15.5 cm
Package 1 Weight	42 g

Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	6 cm
Package 2 Width	10.5 cm
Package 2 Length	21.5 cm
Package 2 Weight	475 g
Unit Type of Package 3	CAR
Number of Units in Package 3	300
Package 3 Height	33.5 cm
Package 3 Width	34.5 cm
Package 3 Length	44 cm
Package 3 Weight	15.05 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	3
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	B4bb8a57-d202-4769-a2e0-19cfa1805b08
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No