



generator and differential protection relay, PowerLogic P3G30

P3G32

Main

| Range Of Product | PowerLogic P3 |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Relay Application | Generator |
| Product Reference | P3G32 |
| Device Mounting | Flush |
| Mounting Support | Rack |
| Mounting Mode | Flush mounting |
| Power Supply | 110230 V AC/DC 50/60 Hz tolerance: + 10 % - 15 % 2448 V AC/DC 50/60 Hz tolerance: + 10 % - 15 % |
| Measuring Inputs | : 1/5 A CT 36 : 1/0.2 A CT |
| Number Of Digital Outputs (Do) | 22 digital |
| Communication Protocols | TCP/IP all counters conforming to 60255-5 DNP3 - DNP3 TCP DeviceNet Ethernet IP/Modbus TCP Modbus RTU Profibus DP SPAbus |
| Redundancy Communication Port Protocol | PRP RSTP |
| Cybersecurity | Enable/disable communication ports Firmware signature Password protection Port hardening Role-based access control |

| Protection Functions | Phase overcurrent 50/51 |
|---------------------------------|-------------------------------------------------------------------------------|
| | Phase overcurrent 50/51 22 |
| | Directional phase overcurrent 67 |
| | Earth fault overcurrent 50N/51N Directional earth fault 67N |
| | Transient earth fault 67N |
| | Capacitor bank unbalance 51C |
| | Current protection 46 I2/I1 |
| | Cold load pick-up CPLU 50/51 |
| | Harmonic distortion 50/51 |
| | Circuit breaker protection 50 BF Switch ON to fault (SOTF) 50/51 |
| | Underload 32P |
| | Fault locator 21FL |
| | Recloser 79 |
| | Undercurrent 37 |
| | Locked rotor for starting 48/51LR |
| | Motor restart inhibition 66 Capacitor overvoltage 59C |
| | Negative sequence overcurrent 46 |
| | Overvoltage (L-L or L-N) 59 |
| | Undervoltage (L-L or L-N) 27 |
| | Positive sequence undervoltage 27P |
| | Earth fault overcurrent 51N/51G |
| | Underfrequency 81 Overfrequency 810 |
| | Rate of change of frequency 81R |
| | Synchro-check 25 |
| | Lockout 86 |
| | CT supervision 60 |
| | VT supervision 60 |
| | Programmable stages 99 Programmable curve 99 |
| | Logic selectivity |
| | Excessive starting time, locked rotor 48/51LR |
| | Thermal overload for machines 49T |
| | Underimpedance 21G |
| | Directional active underpower 32P |
| | Field loss (underimpedance) 40 Restricted earth fault 64REF |
| | Pole slip 78PS |
| | Stator earth fault 64S |
| | Differential protection 87M |
| Relay Type | Multifunction control relay |
| Controllable Switchgear Devices | 6 controlled + 8 displayed |
| Number Of Setting Groups | User |
| Monitoring Functions | Trip circuit supervision 74 |
| | Circuit breaker monitoring |
| | Relay self-monitoring |
| Switchgear Diagnosis Type | Cumulative breaking current (2 configurable buttons) |
| | Trip circuit supervision |
| | Nb of operations, operating time, charging time, nb of racking out operations |
| | VT supervision CT supervision |
| Connections - Terminals | Clamps terminal flush mounting |
| | Ring lugs |
| | |
| Complements | |
| Complementary | |

Complementary

| Input Power Interruption | 50 ms |
|--------------------------------|-------------------------------------|
| Maximum Power Consumption In W | 20 W typical 28 W maximum |
| Time Synchronisation Protocol | SNTP IRIG-B |
| Software Name | Easergy SmartApp ESetup Easergy Pro |

| Number Of Key | 2 contextual key |
|-----------------------------|----------------------------------------|
| ······· | 1 home |
| | 1 for LED test |
| | 1 local/remote |
| | 5 for navigation |
| | |
| | 2 for switchgear control |
| Local Signalling | 2 x LED red status and alert |
| | 16 x LED green/red/orange programmable |
| Communication Compatibility | IEC 61850 |
| | Modbus RTU |
| | DNP3 |
| | IEC 60870-5-103 |
| | IEC 61850 goose message |
| | Modbus TCPIP |
| | Modbus |
| | Modebalo |
| Device Connection | Extension port straight |
| | Serial port straight |
| | Serial port fiber optic |
| | Ethernet port straight |
| | Ethernet port fiber optic |
| Standards | EN 60255-26 |
| | EN 60255-27 |
| Height | Total: 177 mm |
| Width | Total: 264 mm |
| Depth | Total : 208 mm |
| Net Weight | 4.2 kg minimum |
| Environment | |

Environment

| Ip Degree Of Protection | IP54 conforming to IEC 60529 |
|-------------------------|------------------------------|
| Relative Humidity | 095 % at -4060 °C |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----|
| Number Of Units In Package 1 | 1 |

Sustainability Screen Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |