Specifications

#### SQUARE D



# Circuit breaker, PowerPacT P, 1200A, 3 pole, 600VAC, 25kA, I-Line, Micrologic 3.0A, 80%, ABC

PJA36120U41A

Product availability: Stock - Normally stocked in distribution facility

### Price\*: 22,845.00 USD

### Main

Range	PowerPact
product name	PowerPact P
Product or Component Type	Circuit breaker
Device Application	Distribution

## 

Complementary		
Line Rated Current	1200 A	
Number of Poles	3P	
Control Type	Toggle	
Breaking capacity code	J	
Breaking capacity	AIR 100 kA 240 V AC 50/60 Hz UL 489 AIR 65 kA 480 V AC 50/60 Hz UL 489 AIR 25 kA 600 V AC 50/60 Hz UL 489 Icu 65 kA 240 V AC 50/60 Hz IEC 60947-2 Icu 50 kA 380/415 V AC 50/60 Hz IEC 60947-2	
[Ue] rated operational voltage	600 V AC 50/60 Hz UL 489	
Network Frequency	50/60 Hz	
[lcs] rated service breaking capacity	35 kA 240 V AC 50/60 Hz IEC 60947-2 25 kA 380/415 V AC 50/60 Hz IEC 60947-2	
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-2	
Trip unit technology	Electronic, ammeter, MicroLogic 3.0 A, LI	
Continuous current rating	80 %	
[Ui] rated insulation voltage	750 V IEC 60947-2	
Trip unit name	MicroLogic 3.0 A	
AWG gauge	4 x AWG 3/0500 kcmil aluminium/copper	
Local signalling	Overload 1 1 LED amber) 1 flag green) Trip causes 4 trip indicator red)	
Mounting mode	I-Line bracket)	
Mounting Support	Bracket	
Electrical connection	I-Line connection, line Lugs, load	
Terminal identifier	AL1200P25K	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Long time pick-up adjustment range	0.41 x lr	
Mounting Height	9 in (228.6 mm)	
Tightening torque	442.5 lbf.in (50 N.m) 0.10.4 in² (95240 mm²) (4 x AWG 3/0500 kcmil) 8.911.5 lbf.in (1.01.3 N.m)	
Number of slots	2 auxiliary switch OF plug-in) 1 alarm switch SD plug-in) 1 overcurrent trip switch SDE plug-in) 1 voltage release MN or MX plug-in)	
Power wire stripping length	1.2 in (30 mm)	
Height	16.16 in (410.46 mm)	
Width	8.27 in (210.06 mm)	
Depth	8.05 in (204.47 mm)	
Product Weight	32 lb(US) (14.5 kg)	
Quantity per Set	1	
Phase connection	ABC	
Circuit breaker application	HACR rated	

## Environment

Quality labels	CE
Standards	UL CSA NEMA NOM-003-SCFI-2000 IEC 60947-2
Product certifications	UL CSA NOM
IP degree of protection	Front cover IP40
Pollution degree	3 IEC 60947-1
Ambient air temperature for operation	-13158 °F (-2570 °C)
Ambient Air Temperature for Storage	-58185 °F (-5085 °C)
Operating altitude	< 6561.68 ft (2000 m) without derating 13123.36 ft (4000 m) with derating

# Ordering and shipping details

Category	US10DE201210	
Discount Schedule	0DE2	
GTIN	00785901879336	
Returnability	No	
Country of origin	US	

# **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	12.70 in (32.258 cm)	
Package 1 Width	12.00 in (30.48 cm)	

Package 1 Length

20.50 in (52.07 cm)

Package 1 Weight

32.0001 lb(US) (14.515 kg)

# **Contractual warranty**

Warranty

18 months

## Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability  $\geq$ 

${\mathcal O}$ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	2496
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

### Use Again

$\circlearrowright$ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	No