

PratiKa wander socket - straight - 32 A - 3P + E - 380...415 V AC - IP67

PKF32M734

Main

| Range | Mureva |
|---------------------------|---------------|
| Product Or Component Type | Wander socket |
| Device Short Name | Mureva screw |
| Plug, Socket Category | Low voltage |
| Poles Description | 3P + E |
| Network Type | AC |
| Outlet Standard | Industrial |

Complementary

| Plug, Socket, Control Station Shape | Straight |
|-------------------------------------|---|
| [In] Rated Current | 32 A |
| [Ue] Rated Operational Voltage | 380415 V |
| Network Frequency | 50/60 Hz |
| Ground Lug Clockwise Position | 6 h |
| Plug, Socket Material | Housing: self-extinguishing engineering polymer |
| Contacts Material | Sleeves: brass |
| Connections - Terminals | Captive screws |
| Cable Cross Section | 2.510 mm² |
| Cable Outer Diameter | 11.521 mm |
| Cable Entry | Cable gland |
| Thread Type | Pg 21 |
| Net Weight | 0.3 kg |
| Height | 99 mm |
| Width | 99 mm |
| Depth | 164 mm |
| Colour | Grey (RAL 7035) |
| Voltage Colour | Red |

Environment

| Standards | IEC 60309-1 IEC 60309-2 |
|-------------------------|------------------------------|
| Ip Degree Of Protection | IP67 conforming to IEC 60529 |

| Ik Degree Of Protection | IK08 conforming to EN 62262 |
|---------------------------------------|------------------------------------|
| Fire Resistance | 850 °C conforming to IEC 60695-2-1 |
| Relative Humidity | 50 % at 40 °C |
| | 70 % at 30 °C |
| | 90 % at 20 °C |
| Ambient Air Temperature For Operation | 35 °C (86400 s) -2540 °C |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|---------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 9.5 cm |
| Package 1 Width | 9 cm |
| Package 1 Length | 17.3 cm |
| Package 1 Weight | 282 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 6 |
| Package 2 Height | 17 cm |
| Package 2 Width | 26 cm |
| Package 2 Length | 27 cm |
| Package 2 Weight | 1.87 kg |
| Unit Type Of Package 3 | S03 |
| Number Of Units In Package 3 | 12 |
| Package 3 Height | 30 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 4.24 kg |
| | |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more >

| Circularity Profile | No need of specific recycling operations |
|-----------------------|---|
| | Product out of China RoHS scope. Substance declaration for your information |
| China Rohs Regulation | China RoHS declaration |
| | EU RoHS Declaration |
| Eu Rohs Directive | Compliant |
| Reach Regulation | REACh Declaration |