

# Product data sheet

Specifications

SQUARE D



Mini circuit breaker, QO, 25A, 1 pole, 120/240VAC, 10kA, plug in

QO125

## Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	25 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Pressure plate

## Complementary

Interrupt Rating	10 kA 120/240 V AC 10 kA 120 V AC
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper or aluminum
Tightening Torque	35.4 lbf.in (4 N.m)
Height	3.0 in (76 mm)
Width	0.7 in (19 mm)
Depth	2.9 in (74 mm)
Product weight	0.269 lb(US) (0.122 kg)

## Environment

Certifications	UL listed CSA
Ambient Rating	104 °F (40 °C)

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.80 in (2.032 cm)
Package 1 Width	3.10 in (7.874 cm)
Package 1 Length	3.20 in (8.128 cm)

---

Package 1 Weight 4.32 oz (122.47 g)

## Contractual warranty

---

Warranty 18 months

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	18
--	----

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	---

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard	No
--	----

Packaging without single use plastic	Yes
--------------------------------------	-----

SCIP Number	Af42fb01-813d-40c0-ae28-b8b3299dbc99
-------------	--------------------------------------

China RoHS Regulation	<a href="#">China RoHS declaration</a>
-----------------------	--

### Use Again

#### Repack and remanufacture

Circularity Profile	No need of specific recycling operations
---------------------	--

Halogen content performance	Halogen free product
-----------------------------	----------------------

Take-back	No
-----------	----