

Product data sheet

Specifications



[TAA] Mini circuit breaker, QO, 30A, 2 pole, 120/240VAC, 10kA, plug in, 6mA grd fault A, pigtail

QO230GFI

Product availability: Stock - Normally stocked in distribution facility

Price*: 413.00 USD

Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	30 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	2P
Circuit Breaker Type	Ground fault protecting class A 6 mA
Ratings	Not rated
Electrical Connection	Pressure plate

Complementary

Interrupt Rating	10 kA 120/240 V AC 10 kA 120 V AC
Number of Panel Spaces	2
Wire Size	AWG 14...AWG 8 copper AWG 12...AWG 8 aluminium
Tightening Torque	35.4 lbf.in (4 N.m) 40.7 lbf.in (4.6 N.m) 0.006...0.03 in ² (4...20 mm ²) (AWG 12...AWG 4)
Height	4.1 in (105 mm)
Width	1.5 in (38 mm)
Depth	2.9 in (74 mm)
Net Weight	0.721 lb(US) (0.327 kg)

Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US1DE2A00003
Discount Schedule	DE2A
GTIN	785901563006

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.20 in (5.588 cm)
Package 1 Width	3.70 in (9.398 cm)
Package 1 Length	5.40 in (13.716 cm)
Package 1 Weight	15.200 oz (430.912 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	33
Package 2 Height	5.50 in (13.970 cm)
Package 2 Width	13.70 in (34.798 cm)
Package 2 Length	20.80 in (52.832 cm)
Package 2 Weight	31.601 lb(US) (14.334 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	41
--	----

Environmental Disclosure	Product Environmental Profile
--------------------------	---

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
--	----

Packaging without single use plastic	Yes
--------------------------------------	-----

EU RoHS Directive	Compliant with Exemptions
-------------------	---------------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

China RoHS Regulation	China RoHS declaration
-----------------------	--

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
---------------------------	--

Use Again

Repack and remanufacture


Circularity Profile	End of Life Information
---------------------	---

Take-back

No

Technical Illustration

Dimensions



Technical Illustration

Wiring diagram




Image of product / Alternate images

Alternative

QO™

QO230GFIC

30A

120/240 VAC ~ 60 Hz
10,000 AIR/A nom.I

2 Poles
Polos
Pôles

Pigtail
Cable Neutro
Câble de neutre

Ground fault protection
Protección para la fuga a tierra
Protection contre les défauts à la terre

Ideal for wet and damp locations

Visi-Trip™ indicates tripped circuit

UL943 Class A GFI - Shock Protection