

Mini CB, QO, 90 A, 2P, 120/240 V, 22 kA, Bolt on

QOB290VH

Discontinued on: May 1, 2024

① To be discontinued

Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	90 A
Voltage Rating	120/240 V AC 240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box luas

Complementary

Interrupt Rating	22 kA at 120/240 V AC 22 kA at 240 V AC 22 kA at 120 V AC
Number of Panel Spaces	2
Wire Size	AWG 4AWG 2/0 copper or aluminium
Tightening Torque	5.6 N.m
Height	89 mm
Width	38 mm
Depth	74 mm
Net weight	0.322 kg

Environment

Certifications	UL listed CSA	
Ambient Rating	40 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.810 cm

List Price displayed is VAT EXCLUSIVE.

Package 1 Width	8.636 cm
Package 1 Length	10.922 cm
Package 1 Weight	330.215 g
Unit Type of Package 2	CAR
Number of Units in Package 2	51
Package 2 Height	11.430 cm
Package 2 Width	38.100 cm
Package 2 Length	55.880 cm
Package 2 Weight	16.833 kg

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental Disclosure	Product Environmental Profile

Use Better

No
Yes
Compliant
Af42fb01-813d-40c0-ae28- b8b3299dbc99
REACh Declaration
China RoHS declaration

Use Again


○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

Take-back

No

Technical Illustration

Dimensions



Dimensions are approximate. Refer to technical documentation for additional det