



## MATERIAL FACT SHEET

### 605221 R60TCTRT2TT2-TS

#### General Data

Product Hierarchy	IAD51401
	Modular PLC
	IQ-R Standard
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000605221](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000605221)

#### FA-MOD PLC: Temperature Module

Series	MELSEC IQ-R SERIES
Type	TEMPERATURE CONTROL
Occupied I/O Points on PLC	16
Integrated Analogue Inputs	4
Input Type	THERMOCOUPLE,RTD
Applicable RTD Type	JPT100
Applicable RTD Type (2)	PT100
Applicable Thermocouple Type	B
Applicable Thermocouple Type (2)	E
Applicable Thermocouple Type (3)	J
Applicable Thermocouple Type (4)	K
Applicable Thermocouple Type (5)	L
Applicable Thermocouple Type (6)	N
Applicable Thermocouple Type (7)	PLII
Applicable Thermocouple Type (8)	R
Applicable Thermocouple Type (9)	S
Applicable Thermocouple Type (10)	T
Applicable Thermocouple Type (11)	U
Applicable Thermocouple Type (12)	W5RE/W26RE
Int. Current Consumption (A)	0,28A

#### Product Dimensions & Weight

Width (mm)	27,8
Height (mm)	106
Depth (mm)	141
Weight (kg)	0,24

#### Logistic Dimensions & Gross Weight

Length (cm)	18,0
Width (cm)	15,0
Height (cm)	15,0
Gross Weight (kg)	0,369
Volume (cdm)	4,050

#### Stock Data

Planned Delivery Time (Days)	136
------------------------------	-----

#### Life Cycle

Sales Start	30.08.2021
Predecessor	No Predecessor

#### Additional Product Information

Binding Tariff Information	DEBTI-10685/21-1
BTI validity date	31.10.2024
Battery included	NO

**Export Data**

Commodity Code	85389099
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

**Environmental**

Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

**Conformity**

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	NON-COMPLIANT
UKCA	COMPLIANT

**Documentation & Media Data**

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=R60TCRT2TT2-TS&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=R60TCRT2TT2-TS&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=R60TCRT2TT2-TS&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=R60TCRT2TT2-TS&amp;doc-lang=en</a>
CAD URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=R60TCRT2TT2-TS&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=R60TCRT2TT2-TS&amp;doc-lang=en</a>

**Product Packaging**

Cardboard (g)	75,0
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	3,0
Wood (g)	0
Glass (g)	0
Others (g)	36,0