

Resi9 - comb busbar - 1L+N - 18 mm pitch - 57 modules - 63 A



Main

Range	Resi9	
Product or component type	Comb busbar	
mounting mode	Horizontal	
Accessory / separate part category	Connection accessory	
Lines description	1L + N	
Length in 18 mm modules	57	

Complementary Number of ways

Number of ways	28 ways N + 1 L	
Poles configuration for 1 way	1 x 1P + N 1 x 2P	
Connection pitch	18 mm	
Connector type	Fork	
Distance between way	36 mm	
Marking	L1 L2	
Insulation	Insulated	
device presentation	entation Cuttable	
[le] rated operational current	t 63 A at 40 °C	
[Ue] rated operational voltage	230 V AC Ph/N	
[Ui] rated insulation voltage	500 V AC	
Mounting location	Bottom on biconnect	
9 mm pitches	114	
Width	1000 mm	
Colour	White (RAL 9003)	
Range compatibility	Acti9 Acti9 K60 Resi9 Resi9 MCB Resi9 Resi9 RCBO Resi9 Resi9 RCCB Resi9 Resi9 RSCB	

Environment

Standards	EN/IEC 61439-1	
Product certifications	CE	
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1	

Pollution degree

3

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.600 cm	
Package 1 Width	1.600 cm	
Package 1 Length	101.700 cm	
Package 1 Weight	1 Weight 326.000 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	5	
Package 2 Height	5.500 cm	
Package 2 Width	107.000 cm	
Package 2 Length	8.800 cm	
Package 2 Weight	1.830 kg	
Unit Type of Package 3	P12	
Number of Units in Package 3	270	
Package 3 Height	75.000 cm	
Package 3 Width	80.000 cm	
Package 3 Length	120.000 cm	
Package 3 Weight	117.000 kg	

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
Ø	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations