

Resi9 - comb busbar - 3L+N - 18 mm pitch - 57 modules - 63 A



Main

Range	Resi9
Product or component type	Comb busbar
mounting mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	3L + N
Length in 18 mm modules	57

Complementary Number of ways

Number of ways	14 ways N + 3 L	
Poles configuration for 1 way	1 x 3P + N 1 x 4P	
Connection pitch	18 mm	
Connector type	Fork	
Distance between way	72 mm	
Marking	N L1 L2 L3	
Insulation	Insulated	
device presentation	Cuttable	
[le] rated operational current	63 A at 40 °C	
[Ue] rated operational voltage	230 V AC Ph/N 400 V AC Ph/Ph	
[Ui] rated insulation voltage	500 V AC	
Mounting location	Bottom on biconnect	
9 mm pitches	114	
Width	1000 mm	
Colour	White (RAL 9003)	
Range compatibility	Acti9 Acti9 K60 Resi9 Resi9 MCB Resi9 Resi9 RCBO Resi9 Resi9 RCCB Resi9 Resi9 SWITCH	

Environment

Standards	EN/IEC 61439-1
Product certifications	CE

Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2 cm
Package 1 Width	2 cm
Package 1 Length	100 cm
Package 1 Weight	518 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	5.5 cm
Package 2 Width	106.5 cm
Package 2 Length	9 cm
Package 2 Weight	2.77 kg
Unit Type of Package 3	P12
Number of Units in Package 3	180
Package 3 Height	43 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	117 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
Ø	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations