

Socket with clamp, Harmony, for RXG1 relays, 10A, screw connectors, separate contact

RGZE1S35M

Product availability: Stock - Normally stocked in distribution

Price*: 2.80 USD

| wair | | V | | a | ı | r | |
|------|--|---|--|---|---|---|--|
|------|--|---|--|---|---|---|--|

| Range of Product | Harmony Electromechanical Relays |
|------------------------------|----------------------------------|
| Product or Component Type | Socket |
| Contact terminal arrangement | Separate |

| Complementary | |
|--|---|
| Product compatibility | Plug-in relay RXG 1 C/O |
| [Ui] Rated Insulation Voltage | 250 V |
| [Uimp] rated impulse withstand voltage | 6 kV between coil and contact with reinforced insulation 4 kV between contacts with basic insulation 4 kV between terminals and DIN rail with basic insulation |
| Line Rated Current | 10 A |
| [Ue] rated operational voltage | 250 V IEC 300 V UL |
| Dielectric strength | 5 kV between coil and contact with reinforced insulation 2.5 kV between contacts with basic insulation 3 kV between terminals and DIN rail with basic insulation |
| Connections - terminals | Screw terminals, 1 x 0.251 x 2.5 mm² AWG 22AWG 14) flexible with cable end Screw terminals, 2 x 0.252 x 1 mm² AWG 22AWG 17) flexible with cable end Screw terminals, 2 x 0.52 x 1.5 mm² AWG 20AWG 16) solid without cable end Screw terminals, 1 x 0.51 x 2.5 mm² AWG 20AWG 14) solid without cable end |
| Screw type | M3 |

Environment

| Ambient Air Temperature for Storage | -40185 °F (-4085 °C) |
|---------------------------------------|--|
| Ambient air temperature for operation | -40158 °F (-4070 °C) |
| Relative humidity | 1085 % |
| Standards | UL 508 CSA C22.2 No 14 IEC 61984 |
| Product Certifications | CE EAC UL CSA DNV-GL |
| IP Degree of Protection | IP20 |

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Overvoltage category | III |
|----------------------|-----|
| Pollution degree | 3 |

Ordering and shipping details

| Category | 21128-ZELIO ICE CUBE RELAY ACCESSORIES | |
|-------------------|--|--|
| Discount Schedule | CP2 | |
| GTIN | 3606480689437 | |
| Returnability | Yes | |
| Country of origin | CN | |

Packing Units


| Unit Type of Package 1 | PCE |
|------------------------------|------------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.46 in (6.25 cm) |
| Package 1 Width | 0.67 in (1.7 cm) |
| Package 1 Length | 3.19 in (8.1 cm) |
| Package 1 Weight | 1.13 oz (32.1 g) |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 3.07 in (7.8 cm) |
| Package 2 Width | 3.31 in (8.4 cm) |
| Package 2 Length | 6.42 in (16.3 cm) |
| Package 2 Weight | 12.91 oz (365.9 g) |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 180 |
| Package 3 Height | 11.81 in (30 cm) |
| Package 3 Width | 11.81 in (30 cm) |
| Package 3 Length | 15.75 in (40 cm) |
| Package 3 Weight | 35.94 lb(US) (16.3 kg) |


Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|--|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov | |
| REACh Regulation | REACh Declaration | |
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration | |
| Toxic heavy metal free | Yes | |
| Mercury free | Yes | |
| China RoHS Regulation | China RoHS declaration | |
| RoHS exemption information | Yes | |
| Environmental Disclosure | Product Environmental Profile | |
| Circularity Profile | No need of specific recycling operations | |

Dimensions Drawings

Dimensions






(1) Maintaining clamp

Connections and Schema

Wiring Diagram



Recommended replacement(s)