# **Product datasheet**

Specification





# Interface plug-in relay, 10 A, 1 CO, clear cover, 230 V AC

RXG15P7

## Main

Range of product	Harmony Electromechanical Relays	
Series name	Interface relay	
Product or component type	Plug-in relay	
Device short name	RXG	
Contacts type and composition	1 C/O	
[Ithe] conventional enclosed	10 A at -4055 °C	

#### **Complementary**

Complementary		
[le] rated operational current	10 A at 30 V (DC) conforming to UL 10 A at 30 V (DC) conforming to IEC 10 A at 250 V (AC) conforming to IEC 10 A at 250 V (AC) conforming to UL	
Electrical durability	100000 cycles for NO resistive load at 55 °C 100000 cycles for NC resistive load at 55 °C	
Coil resistance	23500 Ohm +/- 15 %	
Shock resistance	20 gn in operation 100 gn not in operation	
Mounting position	Any position	
Average consumption in VA	0.82 VA 60 Hz	
Control circuit voltage limits	0.81.1 Uc AC	
[Uc] control circuit voltage 230 V AC 50/60 Hz		
Colour of cover	Transparent	
Drop-out voltage threshold	>= 0.3 Uc AC	
Load current	10 A at 250 V AC	
Minimum switching capacity	500 mW at 100 mA, 5 V DC	
Maximum switching capacity	2500 VA	
Torque value	0.8 N.m	
Contact resistance	100 mOhm	
Insulation resistance	1000 MOhm at 500 V DC	
Electrical insulation class	Class F	
Mechanical durability	10000000 cycles	
Safety reliability data	B10d = 100000	
Operating time	20 ms	

Reset time	20 ms	
Overvoltage category	III	
Maximum switching voltage	250 V AC 30 V DC	
Protection category	RTI	
Operating rate	<= 1800 cycles/hour under load <= 18000 cycles/hour no-load	
Pollution degree	2	
Utilisation coefficient	efficient 20 %	
[Ui] rated insulation voltage	250 V conforming to IEC 300 V conforming to CSA 300 V conforming to UL	
Dielectric strength	1000 V AC between contacts with micro disconnection 5000 V AC between coil and contact with reinforced insulation	
Test levels	Level A group mounting	
device presentation	Complete product	
Contacts material	Silver alloy (AgSnO2In2O3)	
Net weight	0.019 kg	

## **Environment**

Standards	IEC 61810-1	
	CSA C22.2 No 14	
	UL 508	
Product certifications	UL	
	CSA	
	EAC	
	CE	
	DNV-GL	
Ambient air temperature for storage	-4085 °C	
Ambient air temperature for operation	-4070 °C	
IP degree of protection	IP40	
Relative humidity	1085 %	
Vibration resistance	3 gn, amplitude = +/- 0.75 mm (f = 10150 Hz)in operation 5 gn, amplitude = +/- 0.75 mm (f = 10150 Hz)not in operation	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.45 cm
Package 1 Width	9.25 cm
Package 1 Length	8.6 cm
Package 1 Weight	221 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.5 cm
Package 2 Width	7.5 cm
Package 2 Length	8.2 cm

Package 2 Weight	206 g
Unit Type of Package 3	S01
Number of Units in Package 3	240
Package 3 Height	15 cm
Package 3 Width	15 cm
Package 3 Length	40 cm
Package 3 Weight	5.169 kg

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance

<b>Ø</b>	Reach Free Of Svhc	
<b>Ø</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

01-Aug-2024