Product datasheet

Specifications





miniature plug-in relay - Zelio RXM2L - 2 C/O - 48 V DC - 5 A without LED

RXM2LB1ED

() Discontinued on: 20-Oct-2020

() Discontinued

Main

Coil Interference Suppression	Without
Range Of Product	Harmony Relay
Series Name	Miniature
Product Or Component Type	Plug-in relay
Device Short Name	RXM
[Ithe] Conventional Enclosed Thermal Current	5 A at -4055 °C

Complementary

Standard
48 V DC
Without
Without push-button
3.6 kV during 1.2/50 μs conforming to IEC 61810-7
5 A (AC-1/DC-1) NO conforming to IEC 2.5 A (AC-1/DC-1) NC conforming to IEC 1 A at 28 V (DC-13) NO
25 mW subject to switching frequency, environment or expected reliability level etc
20 ms between coil de-energisation and making of the Off-delay contact 20 ms between coil energisation and making of the On-delay contact
21 mm
27 mm
46 mm
5 mA subject to switching frequency, environment or expected reliability level etc
5 V subject to switching frequency, environment or expected reliability level etc
38.452.8 V DC
250 V conforming to IEC
250 V AC 250 V DC
>= 0.1 Uc DC
5 A at 250 V AC 5 A at 28 V DC
1250 VA AC 140 W DC

Average Resistance	2600 Ohm +/- 10 %
Average Coil Consumption	0.9 W, DC
Mechanical Durability	1000000 cycles
Electrical Durability	100000 cycles for resistive load 50000 cycles, 1 A at 28 V, DC-13 NO
Safety Reliability Data	B10d = 100000
Operating Rate	<= 1200 cycles/hour under load <= 18000 cycles/hour no-load
Utilisation Coefficient	20 %
Dielectric Strength	2000 V AC between coil and contact 2000 V AC between poles 1000 V AC between contacts
Protection Category	RTI
Operating Position	Any position
Test Levels	Level A group mounting
Sale Per Indivisible Quantity	10
Contacts Material	Silver alloy (Ag/Ni)
Net Weight	0.033 kg

Environment

Ip Degree Of Protection	IP40 conforming to IEC 60529	
Standards	CE IEC 61810-1 (iss. 2)	
Ambient Air Temperature For Storage	-4085 °C	
Vibration Resistance	3 gn, amplitude = +/- 1 mm (f = 1050 Hz)operating conforming to IEC 60068-2-6 6 gn, amplitude = +/- 1 mm (f = 1050 Hz)not operating conforming to IEC 60068-2-6	
Shock Resistance	10 gn for opening conforming to IEC 60068-2-27 5 gn for closing conforming to IEC 60068-2-27	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance


Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Dimensions Drawings

Dimensions




Pin Side View



Product datasheet

Connections and Schema

Wiring Diagram



Symbols shown in blue correspond to Nema marking.


Product datasheet

Performance Curves

Electrical Durability of Contacts

Durability (inductive load) = durability (resistive load) x reduction coefficient.

For 2 Poles Relay



X : Contact current (A)

Y : Durability (Number of operating cycles)

A : Inductive load


B : Resistive load

Note : These are typical curves, actual durability depends on load, environment, duty cycle, etc.

For inductive load, to increase relay life cycles, please add a proper load protection circuit (eg: RC protection/Varistor/ free Wheeling diode -DC load only-)

Maximum Switching Capacity

For 2 Poles Relay



X : Contact voltage (v)

Y : Contact current (A)

A : Inductive AC load

 ${\bf B}$: Resistive AC load

 $\boldsymbol{\mathsf{C}}$: Inductive DC load

 $\boldsymbol{\mathsf{D}}$: Resistive DC load

Note : These are typical curves, actual durability depends on load, environment, duty cycle, etc.

For inductive load, to increase relay life cycles, please add a proper load protection circuit (eg: RC protection/Varistor/ free Wheeling diode -DC load only-)

For low level loads (below 10mA), we recommend to use RXM*GB series with bifurcated contacts relays instead.