Product datasheet

Specifications





function module, TransferPacT, fire protection, dry contact, passive, input signal

TPCDIO14

Main

Range of product	TransferPacT	
Product or component type	I/O module Dry contact	
Device application	Signalling	

Complementary

• •	
Auxiliary contact composition	1 NO
Signalling function	Fire protection (transfer to off position)
Auxiliary connection terminal	Screw clamp terminal 0.052.6 mm ²
mounting mode	Plug-in
mounting position	Left-bottom
minimum input current	5 mA
[Ui] rated insulation voltage	30 V DC
Tightening torque	0.6 N.m +/- 0.1 N.m
Height	56.5 mm
Width	20 mm
Depth	69 mm
Accessory / separate part category	Signalling accessory

Environment

IP degree of protection	IP20
Pollution degree	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.65 cm
Package 1 Width	6.9 cm
Package 1 Length	2 cm
Package 1 Weight	140 g

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information